

Overview

- Most secure object detection due to the barrier principle
- Manipulation-proof, simple teach-in via qTeach or line teach
- IO-Link for extended parameterization options and additional diagnostic data
- Robust housing with stainless steel spacer sleeves



Picture similar



Technical data

General data

Type	Through beam sensor
Emitter / receiver	Receiver
Light source	Use with pulsed red LED
Actual range Sb	5 m
Nominal range Sn	6 m
Smallest object recognizable typ.	5 mm (0,5 mm with aperture)
Alignment / soiled lens indicator	Flashing output indicator
Output indicator	LED yellow
Power on indication	LED green
Sensitivity adjustment	Teach-in and IO-Link
Suppression of reciprocal influence	Yes

Electrical data

Response time / release time	< 0.5 ms
Jitter	< 0.15 ms
Voltage supply range +Vs	10 ... 30 VDC
Current consumption max. (no load)	20 mA (@ 10 VDC)
Current consumption typ.	16 mA (@ 24 VDC)
Voltage drop Vd	<2 VDC
Output function	Light / dark operate
Output circuit	Push-pull

Electrical data

Output current	50 mA
Short circuit protection	Yes
Reverse polarity protection	Yes

Communication interface

Baud rate	230,4 kBaud (COM 3)
Adjustable parameters	Switching point Time filters LED status indicators Output logic Counter Deactivate the sensor element Find Me function Teach-in mode
IO-Link port type	Class A
Process data length	32 Bit
Process data structure	Bit 0 = SSC1 (presence) Bit 2 = quality Bit 3 = alarm Bit 5 = SSC4 (counter) Bit 16-31 = 16 Bit measurement
Interface	IO-Link V1.1
Additional data	Signal strength Excess gain Operating cycles Device temperature
Cycle time	≥ 0.6 ms

O200.ER-GW1J.72NV/E026


Through beam sensors - miniature

Article number: 11224794


Technical data

Mechanical data		Mechanical data	
Width / diameter	8 mm	Front (optics)	PMMA
Height / length	25.1 mm	Connection types	Flylead connector M8 4 pin, L=200 mm
Depth	14.1 mm	Cable characteristics	PVC / PVC 4 x 0.08 mm ²
Design	Rectangular	Ambient conditions	
Mechanical mounting	Sleeve smooth (stainless steel)	Operating temperature	-25 ... +50 °C
Housing material	Plastic (ASA, PMMA)	Protection class	IP 67


Technical drawings



Connection diagram



Pin assignment



Excess gain curve

