

IR18.P06F-F50.NC1Z.7BCV

Inductive proximity switch - factor 1 - all metals

Article number: 11119473

Overview

- 6 mm
- NPN break function (NC)
- cable, 2 m
- 25 ... 75 °C
- IP 67



Picture similar



Technical data

General data

Mounting type	Flush
Special type	Factor 1
Nominal sensing distance S _n	6 mm
Hysteresis	3 ... 20 % of S _r
Output indicator	LED red

Electrical data

Switching frequency	< 500 Hz
Voltage supply range +V _s	5 ... 36 VDC
Current consumption max. (no load)	12 mA
Output circuit	NPN break function (NC)
Voltage drop V _d	< 2 VDC
Output current	< 200 mA

Electrical data

Short circuit protection	Yes
Reverse polarity protection	Yes

Mechanical data

Type	Cylindrical threaded
Material (sensing face)	PBT
Housing material	Brass nickel plated
Dimension	18 mm
Housing length	50 mm
Connection types	Cable, 2 m
Tightening torque max.	40 Nm

Ambient conditions

Operating temperature	-25 ... +75 °C
Storage temperature	-40 ... +85 °C
Protection class	IP 67

Remarks


- Same sensing distance on all metals (no reduction factor)

IR18.P06F-F50.NC1Z.7BCV

Inductive proximity switch - factor 1 - all metals

Article number: 11119473

Dimension drawing



Connection diagram

