


Magnetic field sensor

MB-15/32GM25-E0-1.27M-4MOL

- Cylindrical housing
- Molex connector
- Hall Effect Sensor
- 3-wire DC

Dimensions



Technical Data

General specifications		
Switching function		Normally open (NO)
Output type		NPN
Output polarity		DC
Output type		3-wire
Nominal ratings		
Operating voltage	U _B	4.5 ... 24 V DC
Operating current	I _L	20 mA max
No-load supply current	I ₀	10 mA max
Ambient conditions		
Ambient temperature		-40 ... 105 °C (-40 ... 221 °F)
Mechanical specifications		
Connection type		fixed cable with plug
Housing material		Aluminum
Sensing face		Aluminum
Degree of protection		IP67
Connector		
Number of pins		3
Connection assembly		Molex connector 39-00-2040 Molex contact 39-00-0139
Cable		
Material		PVC
Color		Gray
Number of cores		3
Core cross section		0.34 mm²
Length	L	1.27 m

Release date: 2023-04-20 Date of issue: 2023-04-20 Filename: 70163065_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com


USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Wiring Diagram



Release date: 2023-04-20 Date of issue: 2023-04-20 Filename: 70163065_eng.pdf