



## SLC445-ER-0810-14-01

- Multifunctional
- Muting
- Cyclic mode
- Double acknowledgement/reset
- Multiscan
- Safety type 4 in accordance with IEC 61496-1
- active integrated set-up tool
- Blanking: fixed/floating
- Status and diagnostics via 7-segment display
- Integrated contactor control
- User-friendly parameter setting, no tools required

## Data

### Ordering data

Product type description	SLC445-ER-0810-14-01
Article number (order number)	103005394
EAN (European Article Number)	4030661436050
eCl@ss number, version 12.0	27-27-27-04
eCl@ss number, version 11.0	27-27-27-04
eCl@ss number, version 9.0	27-27-27-04
ETIM number, version 7.0	EC002549
ETIM number, version 6.0	EC002549

### Approvals - Standards

Certificates

TÜV  
cULus

### General data

Standards	CLC/TS 61496-2 EN IEC 61496-1
Housing material	Aluminium
Reaction time, maximum	20 ms
Gross weight	1,580 g

## General data - Features

Muting function	Yes
Override	Yes
Clock control possible	Yes
Restart interlock (manual reset)	Yes
Contact control integrated	Yes
Beam coding available	Yes
Blanking function	Yes
7-segment display	Yes
Integral system diagnostics, status	Yes
Integral system diagnostics	Yes
Reduced resolution	Yes
Number of fail-safe digital outputs	2
Number of beams	80

## Safety classification

Standards	EN ISO 13849-1 EN IEC 62061
Performance Level, up to	e
Category	4
PFH value	$5.14 \times 10^{-9}$ /h
Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)
Safety type in accordance with IEC 61496-1	4

## Mechanical data

Detection ability for test bodies at $v = 1.6$ m/s	14 mm
Height of the protection field	810 mm
Range, protection field, minimum	0.3 m
Range, protection field, maximum	7 m
Wave length of the laserdiode	880 nm

## Mechanical data - Connection technique

Termination	Connector
Terminal connector, Recipient	Connector plug M12, 12-pole
Terminal, Connector, Transmitter	Connector plug M12, 4-pole
Length of the connectable cable, maximum	100 m

## Mechanical data - Dimensions

Length of sensor	33 mm
Width of sensor	27.8 mm
Height of the Sensor (Receiver)	901 mm
Height of the Sensor (Transmitter)	891 mm

## Ambient conditions

Degree of protection	IP67
Ambient temperature	-25 ... +50 °C
Storage and transport temperature	-25 ... +70 °C
Protection class	III

## Electrical data

Switching voltage OSSD, HIGH signal	24 V
Electrical power consumption of the receiver, maximum	10 W

Electrical power consumption of the transmitter, maximum 5 W

### Electrical data - Safety digital outputs

Output current, (fail-safe output), maximum 0.25 A

Design of control elements p-type

### Scope of delivery

Scope of delivery Kit with 2 mounting angles

### Accessory

Recommended safety switchgear SRB-E 301

### Note

Note (General)  $I_m$  In case of failure (interruption of the 0 V supply) the maximum leakage current is 1 mA.

### Ordering code

Product type description:  
SLC445-E/R(1)-(2)-01

(1)

---

<b>0170</b>	Protection field height 170 mm
<b>0250</b>	Protection field height 250 mm
<b>0330</b>	Protection field height 330 mm
<b>0410</b>	Protection field height 410 mm
<b>0490</b>	Protection field height 490 mm
<b>0570</b>	Protection field height 570 mm
<b>0650</b>	Protection field height 650 mm
<b>0730</b>	Protection field height 730 mm
<b>0810</b>	Protection field height 810 mm

<b>0890</b>	Protection field height 890 mm
<b>0970</b>	Protection field height 970 mm
<b>1050</b>	Protection field height 1050 mm
<b>1130</b>	Protection field height 1130 mm
<b>1210</b>	Protection field height 1210 mm
<b>1290</b>	Protection field height 1290 mm (only for resolution 30 mm, 50 mm)
<b>1370</b>	Protection field height 1370 mm (only for resolution 30 mm, 50 mm)
<b>1450</b>	Protection field height 1450 mm (only for resolution 30 mm, 50 mm)
<b>1530</b>	Protection field height 1530 mm (only for resolution 30 mm, 50 mm)
<b>1610</b>	Protection field height 1610 mm (only for resolution 30 mm, 50 mm)
<b>1690</b>	Protection field height 1690 mm (only for resolution 30 mm, 50 mm)
<b>1770</b>	Protection field height 1770 mm (only for resolution 30 mm, 50 mm)

(2)

<b>14</b>	Resolution 14 mm (Range 0.3 ...) 7 m
<b>30</b>	Resolution 30 mm (Range 0.3 ...) 10 m

## Pictures

### Product picture (catalogue individual photo)



ID: kslc4f37

| 34.2 kB | .png | 74.083 x 158.397 mm - 210 x 449 px - 72 dpi

| 336.4 kB | .jpg | 292.1 x 625.122 mm - 828 x 1772 px - 72 dpi

| 23.1 kB | .jpg | 57.856 x 123.472 mm - 164 x 350 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 20/08/2024, 6:10 am