



BNS 260-02ZG-R 3,0M

- Pre-wired cable
- Thermoplastic enclosure
- small body
- Concealed mounting possible
- 26 mm x 36 mm x 13 mm
- Long life
- no mechanical wear
- Insensitive to transverse misalignment
- Insensitive to soiling

Data

Ordering data

Product type description	BNS 260-02ZG-R 3,0M
Article number (order number)	103038517
EAN (European Article Number)	4030661545998
eCl@ss number, version 12.0	27-27-44-01
eCl@ss number, version 11.0	27-27-24-02
eCl@ss number, version 9.0	27-27-24-02
ETIM number, version 7.0	EC002544
ETIM number, version 6.0	EC002544

Approvals - Standards

Certificates	cULus UKCA
--------------	---------------

General data

Standards	BG-GS-ET-14 EN IEC 60947-5-3
Coding level according to EN ISO 14119	Low
Working principle	Magnetic drive
Installation conditions (mechanical)	quasi-flush
Housing material	Glass-fibre, reinforced thermoplastic

General data - Features

Coding	Yes
Integral system diagnostics, general	Yes
Number of normally closed (NC)	2
Number of safety contacts	2
Number of cable wires	4

Safety classification

Standards	EN ISO 13849-1
Mission time	20 Year(s)

Safety classification - Safety outputs

B _{10D} Normally-closed contact (NC)	25,000,000 Operations
B _{10D} - Value Normally-closed contact/Normally open contact (NC/NO)	25,000,000 Operations

Mechanical data

Actuating element	Magnet
Direction of motion	Head-on to the active surface

Mechanical data - Switching distances according EN IEC 60947-5-3

Note (Switching distance S_n) Axial misalignment, a horizontal and vertical misalignment of the safety sensor and the actuator are tolerated. The possible misalignment depends on the distance of the active surfaces of the sensor and the actuator. The sensor remains active within the tolerance range.

Assured switching distance 5 mm
"ON" S_{ao}

Assured switching distance 15 mm
"OFF" S_{ar}

Mechanical data - Connection technique

Length of cable 3 m

Termination Cable

Wire cross-section 0.25 mm²

Material of the Cable mantle PVC

Mechanical data - Dimensions

Length of sensor 13 mm

Width of sensor 26 mm

Height of sensor 36 mm

Ambient conditions

Degree of protection IP67

Ambient temperature -25 ... +70 °C

Storage and transport temperature -25 ... +70 °C

Resistance to vibrations 10 ... 55 Hz, amplitude 1 mm

Resistance to shock 30 g / 11 ms

Ambient conditions - Insulation values

Rated insulation voltage U_i 75 VDC

Rated impulse withstand voltage U _{imp}	0.8 kV
--	--------

Electrical data

Required rated short-circuit current	100 A
Switching current, maximum	0.01 A
Switching capacity, maximum	0.24 W
Switching element	2 NC contact
Switching frequency, maximum	5 Hz

Scope of delivery

Scope of delivery	Actuator must be ordered separately.
-------------------	--------------------------------------

Accessory

Recommendation (actuator)	BPS 260
Recommended safety switchgear	SRB-E-301ST SRB-E-201LC

Note

Note (General)	Contact symbols shown for the closed condition of the guard device. The contact configuration for versions with or without LED is identical.
----------------	---

Wiring example

Note (Wiring diagram)	The contacts S11-S12 and S21-S22 must be integrated in the safety circuit.
-----------------------	--

Ordering code


Product type description:
BNS 260-(1)(2)Z(3)-(4)-(5)

(1)

11	1 NO contacts/1 NC contact
02	2 NC contact
(2)	
without	with diagnostic output
/01	1 NC contact
(3)	
without	without LED switching conditions display
G	with LED switching conditions display
(4)	
without	Pre-wired cable
ST	with connector
(5)	
L	Door hinge on left-hand side
R	Door hinge on right-hand side


Pictures

Product picture (catalogue individual photo)




ID: kbns2f07
 | 291.7 kB | .jpg | 352.778 x 234.95 mm - 1000 x 666 px - 72 dpi
 | 23.0 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi
 | 35.7 kB | .jpg | 123.472 x 82.197 mm - 350 x 233 px - 72 dpi

Product picture (catalogue individual photo)



ID: kbns2f23
 | 25.0 kB | .png | 74.083 x 51.858 mm - 210 x 147 px - 72 dpi
 | 314.7 kB | .jpg | 352.778 x 246.239 mm - 1000 x 698 px - 72 dpi
 | 38.3 kB | .jpg | 123.472 x 86.078 mm - 350 x 244 px - 72 dpi

Dimensional drawing basic component




ID: kbns2g05
| 37.3 kB | .cdr |
| 4.5 kB | .png | 73.731 x 87.489 mm - 209 x 248 px - 72 dpi
| 131.1 kB | .jpg | 352.425 x 417.336 mm - 999 x 1183 px - 72 dpi

Diagram




ID: kbns2k01
| 18.6 kB | .cdr |
| 60.6 kB | .jpg | 352.778 x 57.503 mm - 1000 x 163 px - 72 dpi
| 3.0 kB | .png | 74.083 x 11.994 mm - 210 x 34 px - 72 dpi

Characteristic curve




ID: kbns2d03
| 18.5 kB | .png | 74.083 x 49.036 mm - 210 x 139 px - 72 dpi
| 200.1 kB | .jpg | 352.778 x 233.892 mm - 1000 x 663 px - 72 dpi

Characteristic curve



ID: kbns2d02
| 19.2 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi
| 200.9 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667 px - 72 dpi

Clipart



ID: kbns2c01
| 20.1 kB | .cdr |
| 1.7 kB | .png | 74.083 x 52.564 mm - 210 x 149 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 23/08/2024, 2:05 pm