



Easy TeSys contactor 3P(3 NO) -AC-3 - <= 440 V 120A - 24 V AC coil

LC1E120B5

Main

Range	Easy TeSys	
Range of product	Easy TeSys Control	
Product or component type	Contactor	
Device short name	LC1E	
contactor application	Motor control Resistive load	
Utilisation category	AC-3 AC-1	
poles description	3P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 50/60 Hz	
[le] rated operational current	ent 120 A (at <55 °C) at <= 440 V AC AC-3 for power circuit 150 A (at <55 °C) at <= 440 V AC AC-1 for power circuit	
[Uc] control circuit voltage	ntrol circuit voltage 24 V AC 50 Hz	

Complementary

Motor power kW	37 kW at 220230 V AC 50/60 Hz (AC-3)
	55 kW at 380400 V AC 50/60 Hz (AC-3)
	59 kW at 415 V AC 50/60 Hz (AC-3)
	59 kW at 440 V AC 50/60 Hz (AC-3)
	75 kW at 500 V AC 50/60 Hz (AC-3)
	80 kW at 660690 V AC 50/60 Hz (AC-3)
Pole contact composition	3 NO
[Ith] conventional free air thermal current	25 A (at 55 °C) for power circuit
Irms rated making capacity	1200 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	960 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	1100 A 40 °C - 10 s for power circuit
Associated fuse rating	250 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC
	60947-5-1
	10 A gG at <= 690 V coordination type 1 for power circuit
Average impedance	0.6 mOhm - Ith 150 A 50 Hz for power circuit
Power dissipation per pole	8.6 W AC-3
	14 W AC-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	8 kV coil not connected to the power circuit conforming to IEC 60947

Mechanical durability	4000000 cycles
Electrical durability	800000 cycles AC-3 250000 cycles AC-1
Control circuit type	AC at 50 Hz
Control circuit voltage limits	0.851.1 Uc (-555 °C):operational 50 Hz 0.350.55 Uc (-555 °C):drop-out 50 Hz
Inrush power in VA	300 VA 50 Hz cos phi 0.8 (at 20 °C) 300 VA 60 Hz cos phi 0.8 (at 20 °C)
Hold-in power consumption in VA	22 VA 50 Hz cos phi 0.3 (at 20 °C) 22 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	38 W for control circuit
Operating time	2050 ms on closing 620 ms on opening
Maximum operating rate	1200 cyc/h 55 °C
Connections - terminals	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 10120 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 20170 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 10120 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 20170 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: solid without cable end
Tightening torque	Power circuit: 12 N.m Control circuit: 1.2 N.m
Auxiliary contact composition	1 NO + 1 NC
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
Mounting support	Plate DIN rail
Environment	
Standards	IEC 60947-1 IEC 60947-4-1 IEC 60947-5-1
product certifications	CE EAC
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH (pollution degree 3) conforming to IEC 60068-2-30
Permissible ambient air temperature around the device	-2070 °C at Uc -6080 °C storage -555 °C operation
Operating altitude	3000 m without derating

Fire resistance	850 °C conforming to IEC 60695-2-1		
Mechanical robustness	Vibrations contactor open (1.5 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor open (7 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms)	ions contactor closed (3 Gn, 5300 Hz) s contactor open (7 Gn for 11 ms)	
Height	158 mm		
Width	120 mm		
Depth	132 mm		
Net weight	2.3 kg		

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.000 cm
Package 1 Width	17.000 cm
Package 1 Length	21.000 cm
Package 1 Weight	2.413 kg
Unit Type of Package 2	P06
Number of Units in Package 2	24
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	66.715 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



LC1E120B5

Technical Illustration

Assembly's dimensions



