

Product datasheet

Specifications



contactor - Easy TeSys - 3P (3 NO) - AC-3 - ≤ 440 V 250 A - 415 V AC coil

LC1E250N5

Main

Range	Easy TeSys
Range of product	Easy TeSys Control
Product or component type	Contactors
Device short name	LC1E
contactor application	Resistive load Motor control
Utilisation category	AC-3 AC-1
poles description	3P
[Ue] rated operational voltage	Power circuit: ≤ 690 V AC 50/60 Hz
[Ie] rated operational current	250 A (at ≤ 55 °C) at ≤ 440 V AC AC-3 for power circuit 300 A (at ≤ 40 °C) at ≤ 440 V AC AC-1 for power circuit
[Uc] control circuit voltage	415 V AC 50 Hz

Complementary

Motor power kW	75 kW at 220...230 V AC 50/60 Hz 132 kW at 380...400 V 140 kW at 415 V 140 kW at 440 V 160 kW at 500 V 160 kW at 660...690 V
Pole contact composition	3 NO
[I _{th}] conventional free air thermal current	36 A (at 55 °C)
I _{rm} s rated making capacity	2500 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	2000 A at 440 V for power circuit conforming to IEC 60947
[I _{cw}] rated short-time withstand current	1800 A 40 °C - 10 s for power circuit
Associated fuse rating	10 A gG at ≤ 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1 315 A gG at ≤ 690 V coordination type 1 for power circuit
Average impedance	0.32 mOhm - I _{th} 300 A 50 Hz for power circuit
Power dissipation per pole	20 W AC-3 29 W AC-1
[U _i] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3
[U _{imp}] rated impulse withstand voltage	8 kV coil not connected to the power circuit conforming to IEC 60947

Mechanical durability	5000000 cycles
Electrical durability	200000 cycles AC-1 700000 cycles AC-3
Control circuit type	AC at 50 Hz
Control circuit voltage limits	0.85...1.1 U _c (-5...55 °C):operational 50 Hz 0.35...0.55 U _c (-5...55 °C):drop-out 50 Hz
Inrush power in VA	805 VA 50 Hz cos phi 0.3 (at 20 °C) 970 VA 60 Hz cos phi 0.3 (at 20 °C)
Hold-in power consumption in VA	55 VA 50 Hz cos phi 0.3 (at 20 °C) 66 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	18...24 W for control circuit
Operating time	20...35 ms on closing 7...15 ms on opening
Maximum operating rate	1200 cyc/h 55 °C
Connections - terminals	Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...4 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 1...4 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 1...2.5 mm ² - cable stiffness: flexible with cable end Power circuit: cable with lug - external diameter: 185 mm Power circuit: bars 2 - busbar cross section: 32 x 4 mm
Tightening torque	Control circuit: 1.2 N.m Power circuit: 35 N.m
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
mounting support	Plate

Environment

Standards	IEC 60947-1 IEC 60947-4-1 IEC 60947-5-1
product certifications	EAC CE
IP degree of protection	IP00 conforming to IEC 60529
Permissible ambient air temperature around the device	-20...70 °C at U _c -60...80 °C storage -5...55 °C operation
Operating altitude	3000 m without derating
Fire resistance	850 °C conforming to IEC 60695-2-1
Mechanical robustness	Vibrations contactor open (1.5 Gn, 5...300 Hz) Vibrations contactor closed (3 Gn, 5...300 Hz) Shocks contactor open (6 Gn for 11 ms) Shocks contactor closed (7 Gn for 11 ms)
Height	197 mm
Width	168.5 mm

Depth	181 mm
-------	--------

Net weight	4.7 kg
------------	--------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	21.5 cm
------------------	---------

Package 1 Width	24.0 cm
-----------------	---------

Package 1 Length	26.0 cm
------------------	---------

Package 1 Weight	5.4 kg
------------------	--------

Unit Type of Package 2	S06
------------------------	-----

Number of Units in Package 2	12
------------------------------	----

Package 2 Height	73.5 cm
------------------	---------

Package 2 Width	60.0 cm
-----------------	---------

Package 2 Length	80.0 cm
------------------	---------

Package 2 Weight	77.8 kg
------------------	---------

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)

Offer Marketing Illustration

Product benefits / Features

Easy TeSys Contactors

- 

Designed for the essential
Deliver the best balance between performance and budget without any compromise on quality
- 

Easy to use
Easier to install and operate with multi-standard screws
- 

Cost-effective
Provides a cost-effective solution to a simple application



Offer Marketing Illustration

Product benefits / Features



The image shows a Schneider Easy TeSys Contactor, a three-phase AC contactor. It is a dark grey plastic component with three main switching contacts on the front. The top has four terminal screws labeled 1, 2, 3, and 4. The bottom has four terminal screws labeled 5, 6, 7, and 8. The Schneider logo and 'Easy TeSys Contactor' are printed on the front. The device is mounted on a DIN rail.

Easy TeSys Contactors

Technical Benefits

- 9 sizes cover common applications from 6 to 630A.
- Designed to meet the requirements of Electro-domestic and HVAC applications.
- Various Relay Coil Voltages: A.C.
- It can cover -5°C to 55°C working temperature and mounted by DIN-rail, No derating up to 3000m altitude.
- 2.2kW to 335kW (AC3/400V)
- Multi-standards certified (IEC, CCC, EAC) and Green Premium compliant (RoHS/Reach).

Offer Marketing Illustration

Product benefits / Features



Technical Illustration

Assembly's dimensions

