

TeSys

Contactor

# eq to 440V, 6A, 1 NC aux, 48VDC coil

Price\*: 75.00 USD

### Main Range

**Product or Component Type** 

Troduct of Component Type	Contactor
Device short name	LP1K
contactor application	Motor control
Complementary	
Utilisation category	AC-3 AC-3e
	AC-4
poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit <= 690 V AC <= 400 Hz Signalling circuit <= 690 V AC <= 400 Hz
[le] rated operational current	6 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 6 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit
Control circuit type DC standard	
[Uc] control circuit voltage	48 V DC
Motor power kW	1.5 kW 220230 V AC 50/60 Hz AC-3 2.2 kW 380415 V AC 50/60 Hz AC-3 3 kW 440/690 V AC 50/60 Hz AC-3 1.5 kW 220230 V AC 50/60 Hz AC-3e 2.2 kW 380415 V AC 50/60 Hz AC-3e 3 kW 440/690 V AC 50/60 Hz AC-3e 1.5 kW 220230 V AC 50/60 Hz AC-3e 3 kW 440/690 V AC 50/60 Hz AC-4 2.2 kW 380415 V AC 50/60 Hz AC-4 3 kW 440/690 V AC 50/60 Hz AC-4
Auxiliary contact composition	1 NC
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	20 A (at 140 °F (60 °C)) for power circuit 10 A (at 122 °F (50 °C)) for signalling circuit
Irms rated making capacity	110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947
Rated breaking capacity	110 A at 220230 V conforming to IEC 60947 110 A at 380400 V conforming to IEC 60947 110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 70 A at 660690 V conforming to IEC 60947

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[lcw] rated short-time withstand	90 A 122 °F (50 °C) - 1 s for power circuit
current	85 A 122 °F (50 °C) - 5 s for power circuit
	80 A 122 °F (50 °C) - 10 s for power circuit
	60 A 122 °F (50 °C) - 30 s for power circuit
	45 A 122 °F (50 °C) - 1 min for power circuit
	40 A 122 °F (50 °C) - 3 min for power circuit
	20 A 122 °F (50 °C) - >= 15 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit
	110 A - 100 ms for signalling circuit
Associated fuse rating	25 A gG at <= 440 V for power circuit
	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947
	10 A gG for signalling circuit conforming to VDE 0660
Average impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit 600 V UL 508
•	Power circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-5-1
	Signalling circuit 600 V UL 508
	Power circuit 600 V CSA C22.2 No 14
	Signalling circuit 600 V CSA C22.2 No 14
Insulation resistance	> 10 MOhm for signalling circuit
Inrush power in W	3 W 68 °F (20 °C))
Hold-in power consumption in W	3 W 68 °F (20 °C)
Heat dissipation	1.3 W
Control circuit voltage limits	Operational: 0.81.15 Uc (at <122 °F (50 °C)) Drop-out: >= 0.10 Uc (at <122 °F (50 °C))
Connections - terminals	screw clamp terminals 1 0.0020.006 in² (1.54 mm²)solid
	screw clamp terminals 1 0.0010.006 in² (0.754 mm²)flexible without cable end
	screw clamp terminals 1 0.00050.004 in² (0.342.5 mm²)flexible with cable end
	screw clamp terminals 2 0.0020.006 in² (1.54 mm²)solid
	screw clamp terminals 2 0.0010.006 in² (0.754 mm²)flexible without cable end
	screw clamp terminals 2 0.00050.002 in² (0.341.5 mm²)flexible with cable end
	Power circuit screw clamp terminals 2 0.002 in <sup>2</sup> (1.5 mm <sup>2</sup> )flexible with cable end
Maximum operating rate	3600 cyc/h
Auxiliary contacts type	Instantaneous 1 NC
Minimum switching current	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Mounting Support	Rail Plate
	Plate
Tightening torque	7.0811.5 lbf.in (0.81.3 N.m) screw clamp terminals Philips No 2
5	7.0811.5 lbf.in (0.81.3 N.m) screw clamp terminals 11mps 10 2
	7.0811.5 lbf.in (0.81.3 N.m) screw clamp terminals pozidriv No 2
Operating time	3040 ms coil energisation and NO closing
	10 ms coil de-energisation and NO opening
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1
Canada Tomada Toyon	B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	10 Mcycles
Electrical durability	1.3 Moveles 6.4 AC-3 <= 440 V
	1.3 Mcycles 6 A AC-3 <= 440 V 1.3 Mcycles 6 A AC-3e <= 440 V
	0.05 Mcycles 36 A AC-3e <= 440 V
	3.55
Height	2.3 in (58 mm)
Width	1.8 in (45 mm)
Depth	2.2 in (57 mm)
Net Weight	0.496 lb(US) (0.225 kg)
	0.100 10(00) (0.220 Ng)

### **Environment**

Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4
Product Certifications	CB Scheme CCC UL CSA EAC CE
IP degree of protection	IP2X
Ambient air temperature for operation	-13122 °F (-2550 °C)
Ambient Air Temperature for Storage	-58176 °F (-5080 °C)
Operating altitude	6561.68 ft (2000 m) without derating
Flame retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102

# Ordering and shipping details

Category	US10l1222321	
Discount Schedule	0112	
GTIN	3389110495249	
Returnability	No	
Country of origin	ID	

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.559 in (6.500 cm)	
Package 1 Width	2.441 in (6.200 cm)	
Package 1 Length	1.890 in (4.800 cm)	
Package 1 Weight	7.725 oz (219.000 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	40	
Package 2 Height	5.906 in (15.000 cm)	
Package 2 Width	11.811 in (30.000 cm)	
Package 2 Length	2 Length 15.748 in (40.000 cm)	
Package 2 Weight 20.227 lb(US) (9.175 kg)		

# **Contractual warranty**

# Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes


#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov


**Dimensions Drawings** 

#### **Dimensions**

#### Contactors LC1 K, LP1 K, LP4 K: Mounting on Panel



#### Contactors LC1 K, LP1 K, LP4 K: Mounting on Rail AM1 DP200 or AM1 DE200 (35 mm)




### **Product data sheet**

### **LP1K0601ED**

Connections and Schema

Wiring

3-Pole Contactors: 3P + N/O



3-Pole Contactors: 3P + N/C

