

Siemens  
EcoTech



power contactor, AC-3e/AC-3 115 A, 55 kW / 400 V, AC (50-60 Hz) / DC U<sub>c</sub>: 110-127 V 3-pole, auxiliary contacts 2 NO + 2 NC drive: conventional main circuit: busbar control and auxiliary circuit: screw terminal



|                                                                                                              |                            |
|--------------------------------------------------------------------------------------------------------------|----------------------------|
| product brand name                                                                                           | SIRIUS                     |
| product designation                                                                                          | Power contactor            |
| product type designation                                                                                     | 3RT1                       |
| General technical data                                                                                       |                            |
| size of contactor                                                                                            | S6                         |
| product extension                                                                                            |                            |
| • function module for communication                                                                          | No                         |
| • auxiliary switch                                                                                           | Yes                        |
| power loss [W] for rated value of the current                                                                |                            |
| • at AC in hot operating state                                                                               | 21 W                       |
| • at AC in hot operating state per pole                                                                      | 7 W                        |
| • without load current share typical                                                                         | 5.2 W                      |
| type of calculation of power loss depending on pole                                                          | quadratic                  |
| insulation voltage                                                                                           |                            |
| • of main circuit with degree of pollution 3 rated value                                                     | 1 000 V                    |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 500 V                      |
| surge voltage resistance                                                                                     |                            |
| • of main circuit rated value                                                                                | 8 kV                       |
| • of auxiliary circuit rated value                                                                           | 6 kV                       |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 690 V                      |
| shock resistance at rectangular impulse                                                                      |                            |
| • at AC                                                                                                      | 8,5g / 5 ms, 4,2g / 10 ms  |
| • at DC                                                                                                      | 8,5g / 5 ms, 4,2g / 10 ms  |
| shock resistance with sine pulse                                                                             |                            |
| • at AC                                                                                                      | 13,4g / 5 ms, 6,5g / 10 ms |
| • at DC                                                                                                      | 13,4g / 5 ms, 6,5g / 10 ms |
| mechanical service life (operating cycles)                                                                   |                            |
| • of contactor typical                                                                                       | 10 000 000                 |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000                  |
| • of the contactor with added auxiliary switch block typical                                                 | 10 000 000                 |
| reference code according to IEC 81346-2                                                                      | Q                          |
| Substance Prohibition (Date)                                                                                 |                            |
| SVHC substance name                                                                                          | Lead - 7439-92-1           |
| Weight                                                                                                       | 3.28 kg                    |
| Ambient conditions                                                                                           |                            |
| installation altitude at height above sea level maximum                                                      | 2 000 m                    |

|                                                                        |                    |
|------------------------------------------------------------------------|--------------------|
| <b>ambient temperature</b>                                             |                    |
| • during operation                                                     | -25 ... +60 °C     |
| • during storage                                                       | -55 ... +80 °C     |
| <b>relative humidity minimum</b>                                       | 10 %               |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>  | 95 %               |
| <b>Main circuit</b>                                                    |                    |
| <b>number of poles for main current circuit</b>                        | 3                  |
| <b>number of NO contacts for main contacts</b>                         | 3                  |
| <b>operating voltage</b>                                               |                    |
| • at AC-3 rated value maximum                                          | 1 000 V            |
| • at AC-3e rated value maximum                                         | 1 000 V            |
| <b>operational current</b>                                             |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 160 A              |
| • at AC-1                                                              |                    |
| — up to 690 V at ambient temperature 40 °C rated value                 | 160 A              |
| — up to 690 V at ambient temperature 60 °C rated value                 | 140 A              |
| — up to 1000 V at ambient temperature 40 °C rated value                | 80 A               |
| — up to 1000 V at ambient temperature 60 °C rated value                | 80 A               |
| • at AC-3                                                              |                    |
| — at 400 V rated value                                                 | 115 A              |
| — at 500 V rated value                                                 | 115 A              |
| — at 690 V rated value                                                 | 115 A              |
| — at 1000 V rated value                                                | 53 A               |
| • at AC-3e                                                             |                    |
| — at 400 V rated value                                                 | 115 A              |
| — at 500 V rated value                                                 | 115 A              |
| — at 690 V rated value                                                 | 115 A              |
| — at 1000 V rated value                                                | 53 A               |
| • at AC-4 at 400 V rated value                                         | 97 A               |
| • at AC-5a up to 690 V rated value                                     | 140 A              |
| • at AC-5b up to 400 V rated value                                     | 95 A               |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=20 rated value                  | 115 A              |
| — up to 400 V for current peak value n=20 rated value                  | 115 A              |
| — up to 500 V for current peak value n=20 rated value                  | 115 A              |
| — up to 690 V for current peak value n=20 rated value                  | 115 A              |
| — up to 1000 V for current peak value n=20 rated value                 | 53 A               |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=30 rated value                  | 98 A               |
| — up to 400 V for current peak value n=30 rated value                  | 98 A               |
| — up to 500 V for current peak value n=30 rated value                  | 98 A               |
| — up to 690 V for current peak value n=30 rated value                  | 98 A               |
| — up to 1000 V for current peak value n=30 rated value                 | 53 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 70 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                    |
| • at 400 V rated value                                                 | 54 A               |
| • at 690 V rated value                                                 | 48 A               |
| <b>operational current</b>                                             |                    |
| • at 1 current path at DC-1                                            |                    |
| — at 24 V rated value                                                  | 160 A              |
| — at 60 V rated value                                                  | 160 A              |
| — at 110 V rated value                                                 | 18 A               |
| — at 220 V rated value                                                 | 3.4 A              |
| — at 440 V rated value                                                 | 0.8 A              |

|                                                                    |            |
|--------------------------------------------------------------------|------------|
| — at 600 V rated value                                             | 0.5 A      |
| ● <b>with 2 current paths in series at DC-1</b>                    |            |
| — at 24 V rated value                                              | 160 A      |
| — at 60 V rated value                                              | 160 A      |
| — at 110 V rated value                                             | 160 A      |
| — at 220 V rated value                                             | 20 A       |
| — at 440 V rated value                                             | 3.2 A      |
| — at 600 V rated value                                             | 1.6 A      |
| ● <b>with 3 current paths in series at DC-1</b>                    |            |
| — at 24 V rated value                                              | 160 A      |
| — at 60 V rated value                                              | 160 A      |
| — at 110 V rated value                                             | 160 A      |
| — at 220 V rated value                                             | 160 A      |
| — at 440 V rated value                                             | 11.5 A     |
| — at 600 V rated value                                             | 4 A        |
| ● <b>at 1 current path at DC-3 at DC-5</b>                         |            |
| — at 24 V rated value                                              | 160 A      |
| — at 60 V rated value                                              | 7.5 A      |
| — at 220 V rated value                                             | 0.6 A      |
| — at 440 V rated value                                             | 0.17 A     |
| — at 600 V rated value                                             | 0.12 A     |
| ● <b>with 2 current paths in series at DC-3 at DC-5</b>            |            |
| — at 24 V rated value                                              | 160 A      |
| — at 60 V rated value                                              | 160 A      |
| — at 110 V rated value                                             | 160 A      |
| — at 220 V rated value                                             | 2.5 A      |
| — at 440 V rated value                                             | 0.65 A     |
| — at 600 V rated value                                             | 0.37 A     |
| ● <b>with 3 current paths in series at DC-3 at DC-5</b>            |            |
| — at 24 V rated value                                              | 160 A      |
| — at 60 V rated value                                              | 160 A      |
| — at 110 V rated value                                             | 160 A      |
| — at 220 V rated value                                             | 160 A      |
| — at 440 V rated value                                             | 1.4 A      |
| — at 600 V rated value                                             | 0.75 A     |
| <b>operating power</b>                                             |            |
| ● <b>at AC-3</b>                                                   |            |
| — at 230 V rated value                                             | 37 kW      |
| — at 400 V rated value                                             | 55 kW      |
| — at 500 V rated value                                             | 75 kW      |
| — at 690 V rated value                                             | 110 kW     |
| — at 1000 V rated value                                            | 75 kW      |
| ● <b>at AC-3e</b>                                                  |            |
| — at 230 V rated value                                             | 37 kW      |
| — at 400 V rated value                                             | 55 kW      |
| — at 500 V rated value                                             | 75 kW      |
| — at 690 V rated value                                             | 110 kW     |
| — at 1000 V rated value                                            | 75 kW      |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> |            |
| ● <b>at 400 V rated value</b>                                      | 29 kW      |
| ● <b>at 690 V rated value</b>                                      | 48 kW      |
| <b>operating apparent power at AC-6a</b>                           |            |
| ● up to 230 V for current peak value n=20 rated value              | 40 000 kVA |
| ● up to 400 V for current peak value n=20 rated value              | 80 000 VA  |
| ● up to 500 V for current peak value n=20 rated value              | 100 000 VA |
| ● up to 690 V for current peak value n=20 rated value              | 130 000 VA |
| ● up to 1000 V for current peak value n=20 rated value             | 90 000 VA  |
| <b>operating apparent power at AC-6a</b>                           |            |
| ● up to 230 V for current peak value n=30 rated value              | 30 000 VA  |
| ● up to 400 V for current peak value n=30 rated value              | 60 000 VA  |

|                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• up to 500 V for current peak value n=30 rated value</li> <li>• up to 690 V for current peak value n=30 rated value</li> <li>• up to 1000 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                          | 80 000 VA<br>110 000 VA<br>90 000 VA                                                                                                                                                                                                                                                                                |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>• limited to 1 s switching at zero current maximum</li> <li>• limited to 5 s switching at zero current maximum</li> <li>• limited to 10 s switching at zero current maximum</li> <li>• limited to 30 s switching at zero current maximum</li> <li>• limited to 60 s switching at zero current maximum</li> </ul> | 2 565 A; Use minimum cross-section acc. to AC-1 rated value<br>1 654 A; Use minimum cross-section acc. to AC-1 rated value<br>1 170 A; Use minimum cross-section acc. to AC-1 rated value<br>729 A; Use minimum cross-section acc. to AC-1 rated value<br>572 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>• at AC</li> <li>• at DC</li> </ul>                                                                                                                                                                                                                                                                                                                   | 2 000 1/h<br>2 000 1/h                                                                                                                                                                                                                                                                                              |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>• at AC-1 maximum</li> <li>• at AC-2 maximum</li> <li>• at AC-3 maximum</li> <li>• at AC-3e maximum</li> <li>• at AC-4 maximum</li> </ul>                                                                                                                                                                                                                     | 800 1/h<br>400 1/h<br>1 000 1/h<br>1 000 1/h<br>130 1/h                                                                                                                                                                                                                                                             |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                     |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                                                                                                                                                                                            | AC/DC                                                                                                                                                                                                                                                                                                               |
| <b>control supply voltage at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> <li>• at 60 Hz rated value</li> </ul>                                                                                                                                                                                                                                                                                    | 110 ... 127 V<br>110 ... 127 V                                                                                                                                                                                                                                                                                      |
| <b>control supply voltage at DC rated value</b>                                                                                                                                                                                                                                                                                                                                                                                 | 110 ... 127 V                                                                                                                                                                                                                                                                                                       |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b> <ul style="list-style-type: none"> <li>• initial value</li> <li>• full-scale value</li> </ul>                                                                                                                                                                                                                                             | 0.8<br>1.1                                                                                                                                                                                                                                                                                                          |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                          | 0.8 ... 1.1<br>0.8 ... 1.1                                                                                                                                                                                                                                                                                          |
| <b>design of the surge suppressor</b>                                                                                                                                                                                                                                                                                                                                                                                           | with varistor                                                                                                                                                                                                                                                                                                       |
| <b>apparent pick-up power</b> <ul style="list-style-type: none"> <li>• at minimum rated control supply voltage at AC <ul style="list-style-type: none"> <li>— at 50 Hz</li> <li>— at 60 Hz</li> </ul> </li> <li>• at maximum rated control supply voltage at AC <ul style="list-style-type: none"> <li>— at 60 Hz</li> <li>— at 50 Hz</li> </ul> </li> </ul>                                                                    | 250 VA<br>250 VA<br>300 VA<br>300 VA                                                                                                                                                                                                                                                                                |
| <b>apparent pick-up power of magnet coil at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                                                             | 300 VA<br>300 VA                                                                                                                                                                                                                                                                                                    |
| <b>inductive power factor with closing power of the coil</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                                                   | 0.9<br>0.9                                                                                                                                                                                                                                                                                                          |
| <b>apparent holding power</b> <ul style="list-style-type: none"> <li>• at minimum rated control supply voltage at DC</li> <li>• at maximum rated control supply voltage at DC</li> </ul>                                                                                                                                                                                                                                        | 4.3 VA<br>5.2 VA                                                                                                                                                                                                                                                                                                    |
| <b>apparent holding power</b> <ul style="list-style-type: none"> <li>• at minimum rated control supply voltage at AC <ul style="list-style-type: none"> <li>— at 50 Hz</li> <li>— at 60 Hz</li> </ul> </li> <li>• at maximum rated control supply voltage at AC <ul style="list-style-type: none"> <li>— at 50 Hz</li> <li>— at 60 Hz</li> </ul> </li> </ul>                                                                    | 4.8 VA<br>4.8 VA<br>5.8 VA<br>5.8 VA                                                                                                                                                                                                                                                                                |
| <b>inductive power factor with the holding power of the coil</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                                               | 0.8<br>0.8                                                                                                                                                                                                                                                                                                          |
| <b>closing power of magnet coil at DC</b>                                                                                                                                                                                                                                                                                                                                                                                       | 360 W                                                                                                                                                                                                                                                                                                               |
| <b>holding power of magnet coil at DC</b>                                                                                                                                                                                                                                                                                                                                                                                       | 5.2 W                                                                                                                                                                                                                                                                                                               |

|                                                                    |                                                                                                                          |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| <b>closing delay</b>                                               |                                                                                                                          |
| • at AC                                                            | 20 ... 95 ms                                                                                                             |
| • at DC                                                            | 20 ... 95 ms                                                                                                             |
| <b>opening delay</b>                                               |                                                                                                                          |
| • at AC                                                            | 40 ... 60 ms                                                                                                             |
| • at DC                                                            | 40 ... 60 ms                                                                                                             |
| <b>arcing time</b>                                                 | 10 ... 15 ms                                                                                                             |
| <b>control version of the switch operating mechanism</b>           | Standard A1 - A2                                                                                                         |
| <b>Auxiliary circuit</b>                                           |                                                                                                                          |
| number of NC contacts for auxiliary contacts instantaneous contact | 2                                                                                                                        |
| number of NO contacts for auxiliary contacts instantaneous contact | 2                                                                                                                        |
| operational current at AC-12 maximum                               | 10 A                                                                                                                     |
| <b>operational current at AC-15</b>                                |                                                                                                                          |
| • at 230 V rated value                                             | 6 A                                                                                                                      |
| • at 400 V rated value                                             | 3 A                                                                                                                      |
| • at 500 V rated value                                             | 2 A                                                                                                                      |
| • at 690 V rated value                                             | 1 A                                                                                                                      |
| <b>operational current at DC-12</b>                                |                                                                                                                          |
| • at 24 V rated value                                              | 10 A                                                                                                                     |
| • at 48 V rated value                                              | 6 A                                                                                                                      |
| • at 60 V rated value                                              | 6 A                                                                                                                      |
| • at 110 V rated value                                             | 3 A                                                                                                                      |
| • at 125 V rated value                                             | 2 A                                                                                                                      |
| • at 220 V rated value                                             | 1 A                                                                                                                      |
| • at 600 V rated value                                             | 0.15 A                                                                                                                   |
| <b>operational current at DC-13</b>                                |                                                                                                                          |
| • at 24 V rated value                                              | 10 A                                                                                                                     |
| • at 48 V rated value                                              | 2 A                                                                                                                      |
| • at 60 V rated value                                              | 2 A                                                                                                                      |
| • at 110 V rated value                                             | 1 A                                                                                                                      |
| • at 125 V rated value                                             | 0.9 A                                                                                                                    |
| • at 220 V rated value                                             | 0.3 A                                                                                                                    |
| • at 600 V rated value                                             | 0.1 A                                                                                                                    |
| <b>contact reliability of auxiliary contacts</b>                   | 1 faulty switching per 100 million (17 V, 1 mA)                                                                          |
| <b>UL/CSA ratings</b>                                              |                                                                                                                          |
| <b>full-load current (FLA) for 3-phase AC motor</b>                |                                                                                                                          |
| • at 480 V rated value                                             | 124 A                                                                                                                    |
| • at 600 V rated value                                             | 125 A                                                                                                                    |
| <b>yielded mechanical performance [hp]</b>                         |                                                                                                                          |
| • for single-phase AC motor                                        |                                                                                                                          |
| — at 230 V rated value                                             | 25 hp                                                                                                                    |
| • for 3-phase AC motor                                             |                                                                                                                          |
| — at 200/208 V rated value                                         | 40 hp                                                                                                                    |
| — at 220/230 V rated value                                         | 50 hp                                                                                                                    |
| — at 460/480 V rated value                                         | 100 hp                                                                                                                   |
| — at 575/600 V rated value                                         | 125 hp                                                                                                                   |
| <b>contact rating of auxiliary contacts according to UL</b>        | A600 / Q600                                                                                                              |
| <b>Short-circuit protection</b>                                    |                                                                                                                          |
| <b>design of the fuse link</b>                                     |                                                                                                                          |
| • for short-circuit protection of the main circuit                 |                                                                                                                          |
| — with type of coordination 1 required                             | gG: 355 A (690 V, 100 kA)                                                                                                |
| — with type of assignment 2 required                               | gG: 250 A (690 V, 100 kA), aM: 200 A (690 V, 50 kA), BS88: 250 A (415 V, 50 kA)                                          |
| • for short-circuit protection of the auxiliary switch required    | gG: 10 A (500 V, 1 kA)                                                                                                   |
| <b>Installation/ mounting/ dimensions</b>                          |                                                                                                                          |
| <b>mounting position</b>                                           | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| <b>fastening method</b>                                            | screw fixing                                                                                                             |
| <b>height</b>                                                      | 172 mm                                                                                                                   |
| <b>width</b>                                                       | 120 mm                                                                                                                   |

|                                                                      |                                                                                                              |
|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| <b>depth</b>                                                         | 170 mm                                                                                                       |
| <b>required spacing</b>                                              |                                                                                                              |
| • with side-by-side mounting                                         |                                                                                                              |
| — forwards                                                           | 20 mm                                                                                                        |
| — upwards                                                            | 10 mm                                                                                                        |
| — downwards                                                          | 10 mm                                                                                                        |
| — at the side                                                        | 0 mm                                                                                                         |
| • for grounded parts                                                 |                                                                                                              |
| — forwards                                                           | 20 mm                                                                                                        |
| — upwards                                                            | 10 mm                                                                                                        |
| — at the side                                                        | 10 mm                                                                                                        |
| — downwards                                                          | 10 mm                                                                                                        |
| • for live parts                                                     |                                                                                                              |
| — forwards                                                           | 20 mm                                                                                                        |
| — upwards                                                            | 10 mm                                                                                                        |
| — downwards                                                          | 10 mm                                                                                                        |
| — at the side                                                        | 10 mm                                                                                                        |
| <b>Connections/ Terminals</b>                                        |                                                                                                              |
| <b>type of electrical connection</b>                                 |                                                                                                              |
| • for main current circuit                                           | Connection bar                                                                                               |
| • for auxiliary and control circuit                                  | screw-type terminals                                                                                         |
| • at contactor for auxiliary contacts                                | Screw-type terminals                                                                                         |
| • of magnet coil                                                     | Screw-type terminals                                                                                         |
| <b>width of connection bar</b>                                       | 17 mm                                                                                                        |
| <b>thickness of connection bar</b>                                   | 3 mm                                                                                                         |
| <b>diameter of holes</b>                                             | 9 mm                                                                                                         |
| <b>number of holes</b>                                               | 1                                                                                                            |
| <b>type of connectable conductor cross-sections</b>                  |                                                                                                              |
| • for AWG cables for main contacts                                   | 4 ... 250 kcmil                                                                                              |
| <b>connectable conductor cross-section for main contacts</b>         |                                                                                                              |
| • stranded                                                           | 25 ... 120 mm <sup>2</sup>                                                                                   |
| <b>connectable conductor cross-section for auxiliary contacts</b>    |                                                                                                              |
| • solid or stranded                                                  | 0.5 ... 4 mm <sup>2</sup>                                                                                    |
| • finely stranded with core end processing                           | 0.5 ... 2.5 mm <sup>2</sup>                                                                                  |
| <b>type of connectable conductor cross-sections</b>                  |                                                                                                              |
| • for auxiliary contacts                                             |                                                                                                              |
| — solid                                                              | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ), max. 2x (0.75 ... 4 mm <sup>2</sup> ) |
| — solid or stranded                                                  | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ), max. 2x (0.75 ... 4 mm <sup>2</sup> ) |
| — finely stranded with core end processing                           | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )                                        |
| • for AWG cables for auxiliary contacts                              | 2x (20 ... 16), 2x (18 ... 14), 1x 12                                                                        |
| <b>AWG number as coded connectable conductor cross section</b>       |                                                                                                              |
| • for auxiliary contacts                                             | 18 ... 14                                                                                                    |
| <b>Safety related data</b>                                           |                                                                                                              |
| <b>product function</b>                                              |                                                                                                              |
| • mirror contact according to IEC 60947-4-1                          | Yes                                                                                                          |
| • positively driven operation according to IEC 60947-5-1             | No                                                                                                           |
| • suitable for safety function                                       | Yes                                                                                                          |
| suitability for use safety-related switching OFF                     | Yes                                                                                                          |
| <b>service life maximum</b>                                          | 20 a                                                                                                         |
| <b>test wear-related service life necessary</b>                      | Yes                                                                                                          |
| <b>proportion of dangerous failures</b>                              |                                                                                                              |
| • with low demand rate according to SN 31920                         | 40 %                                                                                                         |
| • with high demand rate according to SN 31920                        | 73 %                                                                                                         |
| <b>B10 value with high demand rate according to SN 31920</b>         | 1 000 000                                                                                                    |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b> | 100 FIT                                                                                                      |
| <b>ISO 13849</b>                                                     |                                                                                                              |
| <b>device type according to ISO 13849-1</b>                          | 3                                                                                                            |
| <b>overdimensioning according to ISO 13849-2 necessary</b>           | Yes                                                                                                          |
| <b>IEC 61508</b>                                                     |                                                                                                              |

|                                                         |                                                                          |
|---------------------------------------------------------|--------------------------------------------------------------------------|
| safety device type according to IEC 61508-2             | Type A                                                                   |
| Electrical Safety                                       |                                                                          |
| protection class IP on the front according to IEC 60529 | IP00; IP20 with box terminal/cover                                       |
| touch protection on the front according to IEC 60529    | finger-safe, for vertical contact from the front with box terminal/cover |
| Approvals Certificates                                  |                                                                          |
| General Product Approval                                |                                                                          |



[Confirmation](#)



[KC](#)

|                          |     |                   |                   |
|--------------------------|-----|-------------------|-------------------|
| General Product Approval | EMV | Functional Safety | Test Certificates |
|--------------------------|-----|-------------------|-------------------|



[Type Examination Certificate](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

|                   |       |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



[Confirmation](#)

|       |         |             |
|-------|---------|-------------|
| other | Railway | Environment |
|-------|---------|-------------|

[Confirmation](#)

[Miscellaneous](#)

[Special Test Certificate](#)



Siemens  
EcoTech



[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1054-6AF36>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1054-6AF36>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1054-6AF36>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)





[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT1054-6AF36&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1054-6AF36&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1054-6AF36/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT1054-6AF36&objecttype=14&gridview=view1>



last modified:



