



power contactor, AC-3e/AC-3, 7 A, 3 kW / 400 V, 3-pole, 24 V DC, with integrated diode, auxiliary contacts: 1 NO, screw terminal, size: S00

|                                                                                                              |                            |
|--------------------------------------------------------------------------------------------------------------|----------------------------|
| product brand name                                                                                           | SIRIUS                     |
| product designation                                                                                          | Power contactor            |
| product type designation                                                                                     | 3RT2                       |
| <b>General technical data</b>                                                                                |                            |
| size of contactor                                                                                            | S00                        |
| product extension                                                                                            |                            |
| • function module for communication                                                                          | No                         |
| • auxiliary switch                                                                                           | Yes                        |
| power loss [W] for rated value of the current                                                                |                            |
| • at AC in hot operating state                                                                               | 0.6 W                      |
| • at AC in hot operating state per pole                                                                      | 0.2 W                      |
| • without load current share typical                                                                         | 4 W                        |
| type of calculation of power loss depending on pole                                                          | quadratic                  |
| insulation voltage                                                                                           |                            |
| • of main circuit with degree of pollution 3 rated value                                                     | 690 V                      |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 690 V                      |
| surge voltage resistance                                                                                     |                            |
| • of main circuit rated value                                                                                | 6 kV                       |
| • of auxiliary circuit rated value                                                                           | 6 kV                       |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V                      |
| shock resistance at rectangular impulse                                                                      |                            |
| • at DC                                                                                                      | 6,7g / 5 ms, 4,2g / 10 ms  |
| shock resistance with sine pulse                                                                             |                            |
| • at DC                                                                                                      | 10,5g / 5 ms, 6,6g / 10 ms |
| mechanical service life (operating cycles)                                                                   |                            |
| • of contactor typical                                                                                       | 30 000 000                 |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000                  |
| • of the contactor with added auxiliary switch block typical                                                 | 10 000 000                 |
| reference code according to IEC 81346-2                                                                      | Q                          |
| Substance Prohibitance (Date)                                                                                |                            |
| SVHC substance name                                                                                          | Lead - 7439-92-1           |
| Weight                                                                                                       | 0.292 kg                   |
| <b>Ambient conditions</b>                                                                                    |                            |
| installation altitude at height above sea level maximum                                                      | 2 000 m                    |
| ambient temperature                                                                                          |                            |
| • during operation                                                                                           | -25 ... +60 °C             |
| • during storage                                                                                             | -55 ... +80 °C             |
| relative humidity minimum                                                                                    | 10 %                       |
| relative humidity at 55 °C according to IEC 60068-2-30                                                       | 95 %                       |

|                                                                        |           |
|------------------------------------------------------------------------|-----------|
| <b>maximum</b>                                                         |           |
| <b>Environmental footprint</b>                                         |           |
| Environmental Product Declaration (EPD)                                | Yes       |
| Global Warming Potential [CO2 eq] total                                | 153 kg    |
| Global Warming Potential [CO2 eq] during manufacturing                 | 1.42 kg   |
| Global Warming Potential [CO2 eq] during operation                     | 152 kg    |
| Global Warming Potential [CO2 eq] after end of life                    | -0.305 kg |
| <b>Main circuit</b>                                                    |           |
| <b>number of poles for main current circuit</b>                        | 3         |
| <b>number of NO contacts for main contacts</b>                         | 3         |
| <b>operating voltage</b>                                               |           |
| • at AC-3 rated value maximum                                          | 690 V     |
| • at AC-3e rated value maximum                                         | 690 V     |
| <b>operational current</b>                                             |           |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 18 A      |
| • at AC-1                                                              |           |
| — up to 690 V at ambient temperature 40 °C rated value                 | 18 A      |
| — up to 690 V at ambient temperature 60 °C rated value                 | 16 A      |
| • at AC-3                                                              |           |
| — at 400 V rated value                                                 | 7 A       |
| — at 500 V rated value                                                 | 6 A       |
| — at 690 V rated value                                                 | 4.9 A     |
| • at AC-3e                                                             |           |
| — at 400 V rated value                                                 | 7 A       |
| — at 500 V rated value                                                 | 6 A       |
| — at 690 V rated value                                                 | 4.9 A     |
| • at AC-4 at 400 V rated value                                         | 6.5 A     |
| • at AC-5a up to 690 V rated value                                     | 15.8 A    |
| • at AC-5b up to 400 V rated value                                     | 5.8 A     |
| • at AC-6a                                                             |           |
| — up to 230 V for current peak value n=20 rated value                  | 4 A       |
| — up to 400 V for current peak value n=20 rated value                  | 4 A       |
| — up to 500 V for current peak value n=20 rated value                  | 3.8 A     |
| — up to 690 V for current peak value n=20 rated value                  | 3.6 A     |
| • at AC-6a                                                             |           |
| — up to 230 V for current peak value n=30 rated value                  | 2.7 A     |
| — up to 400 V for current peak value n=30 rated value                  | 2.7 A     |
| — up to 500 V for current peak value n=30 rated value                  | 2.5 A     |
| — up to 690 V for current peak value n=30 rated value                  | 2.4 A     |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 2.5 mm²   |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |           |
| • at 400 V rated value                                                 | 2.6 A     |
| • at 690 V rated value                                                 | 1.8 A     |
| <b>operational current</b>                                             |           |
| • <b>at 1 current path at DC-1</b>                                     |           |
| — at 24 V rated value                                                  | 15 A      |
| — at 60 V rated value                                                  | 15 A      |
| — at 110 V rated value                                                 | 1.5 A     |
| — at 220 V rated value                                                 | 0.6 A     |
| — at 440 V rated value                                                 | 0.42 A    |
| — at 600 V rated value                                                 | 0.42 A    |
| • <b>with 2 current paths in series at DC-1</b>                        |           |
| — at 24 V rated value                                                  | 15 A      |
| — at 60 V rated value                                                  | 15 A      |
| — at 110 V rated value                                                 | 8.4 A     |
| — at 220 V rated value                                                 | 1.2 A     |
| — at 440 V rated value                                                 | 0.6 A     |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>— at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 0.5 A                                                                                                                                                                                                                                                                                                     |
| <ul style="list-style-type: none"> <li>● <b>with 3 current paths in series at DC-1</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>● <b>at 1 current path at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> </ul> </li> <li>● <b>with 2 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> </ul> </li> <li>● <b>with 3 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul> | 15 A<br>15 A<br>15 A<br>15 A<br>0.9 A<br>0.7 A<br><br>15 A<br>0.35 A<br><br>15 A<br>3.5 A<br>0.25 A<br><br>15 A<br>15 A<br>15 A<br>1.2 A<br>0.14 A<br>0.14 A                                                                                                                                              |
| <b>operating power</b> <ul style="list-style-type: none"> <li>● at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>● at AC-3e <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1.5 kW<br>3 kW<br>3 kW<br>4 kW<br><br>1.5 kW<br>3 kW<br>3 kW<br>4 kW                                                                                                                                                                                                                                      |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>● at 400 V rated value</li> <li>● at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1.15 kW<br>1.15 kW                                                                                                                                                                                                                                                                                        |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=20 rated value</li> <li>● up to 400 V for current peak value n=20 rated value</li> <li>● up to 500 V for current peak value n=20 rated value</li> <li>● up to 690 V for current peak value n=20 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 1.5 kVA<br>2.7 kVA<br>3.3 kVA<br>4.3 kVA                                                                                                                                                                                                                                                                  |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=30 rated value</li> <li>● up to 400 V for current peak value n=30 rated value</li> <li>● up to 500 V for current peak value n=30 rated value</li> <li>● up to 690 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 1 kVA<br>1.8 kVA<br>2.2 kVA<br>2.9 kVA                                                                                                                                                                                                                                                                    |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>● limited to 1 s switching at zero current maximum</li> <li>● limited to 5 s switching at zero current maximum</li> <li>● limited to 10 s switching at zero current maximum</li> <li>● limited to 30 s switching at zero current maximum</li> <li>● limited to 60 s switching at zero current maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 120 A; Use minimum cross-section acc. to AC-1 rated value<br>86 A; Use minimum cross-section acc. to AC-1 rated value<br>67 A; Use minimum cross-section acc. to AC-1 rated value<br>52 A; Use minimum cross-section acc. to AC-1 rated value<br>43 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>● at DC</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 10 000 1/h                                                                                                                                                                                                                                                                                                |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>● at AC-1 maximum</li> <li>● at AC-2 maximum</li> <li>● at AC-3 maximum</li> <li>● at AC-3e maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1 000 1/h<br>750 1/h<br>750 1/h<br>750 1/h                                                                                                                                                                                                                                                                |

|                                                                                       |                                                                   |
|---------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| • at AC-4 maximum                                                                     | 250 1/h                                                           |
| <b>Control circuit/ Control</b>                                                       |                                                                   |
| <b>type of voltage of the control supply voltage</b>                                  | DC                                                                |
| <b>control supply voltage at DC rated value</b>                                       | 24 V                                                              |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b> |                                                                   |
| • initial value                                                                       | 0.8                                                               |
| • full-scale value                                                                    | 1.1                                                               |
| <b>design of the surge suppressor</b>                                                 | diode                                                             |
| <b>closing power of magnet coil at DC</b>                                             | 4 W                                                               |
| <b>holding power of magnet coil at DC</b>                                             | 4 W                                                               |
| <b>closing delay</b>                                                                  |                                                                   |
| • at DC                                                                               | 30 ... 100 ms                                                     |
| <b>opening delay</b>                                                                  |                                                                   |
| • at DC                                                                               | 38 ... 65 ms                                                      |
| <b>arcing time</b>                                                                    | 10 ... 15 ms                                                      |
| <b>control version of the switch operating mechanism</b>                              | Standard A1 - A2                                                  |
| <b>Auxiliary circuit</b>                                                              |                                                                   |
| number of NO contacts for auxiliary contacts instantaneous contact                    | 1                                                                 |
| operational current at AC-12 maximum                                                  | 10 A                                                              |
| <b>operational current at AC-15</b>                                                   |                                                                   |
| • at 230 V rated value                                                                | 10 A                                                              |
| • at 400 V rated value                                                                | 3 A                                                               |
| • at 500 V rated value                                                                | 2 A                                                               |
| • at 690 V rated value                                                                | 1 A                                                               |
| <b>operational current at DC-12</b>                                                   |                                                                   |
| • at 24 V rated value                                                                 | 10 A                                                              |
| • at 48 V rated value                                                                 | 6 A                                                               |
| • at 60 V rated value                                                                 | 6 A                                                               |
| • at 110 V rated value                                                                | 3 A                                                               |
| • at 125 V rated value                                                                | 2 A                                                               |
| • at 220 V rated value                                                                | 1 A                                                               |
| • at 600 V rated value                                                                | 0.15 A                                                            |
| <b>operational current at DC-13</b>                                                   |                                                                   |
| • at 24 V rated value                                                                 | 10 A                                                              |
| • at 48 V rated value                                                                 | 2 A                                                               |
| • at 60 V rated value                                                                 | 2 A                                                               |
| • at 110 V rated value                                                                | 1 A                                                               |
| • at 125 V rated value                                                                | 0.9 A                                                             |
| • at 220 V rated value                                                                | 0.3 A                                                             |
| • at 600 V rated value                                                                | 0.1 A                                                             |
| <b>contact reliability of auxiliary contacts</b>                                      | 1 faulty switching per 100 million (17 V, 1 mA)                   |
| <b>UL/CSA ratings</b>                                                                 |                                                                   |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                   |                                                                   |
| • at 480 V rated value                                                                | 4.8 A                                                             |
| • at 600 V rated value                                                                | 6.1 A                                                             |
| <b>yielded mechanical performance [hp]</b>                                            |                                                                   |
| • for single-phase AC motor                                                           |                                                                   |
| — at 110/120 V rated value                                                            | 0.25 hp                                                           |
| — at 230 V rated value                                                                | 0.75 hp                                                           |
| • for 3-phase AC motor                                                                |                                                                   |
| — at 200/208 V rated value                                                            | 1.5 hp                                                            |
| — at 220/230 V rated value                                                            | 2 hp                                                              |
| — at 460/480 V rated value                                                            | 3 hp                                                              |
| — at 575/600 V rated value                                                            | 5 hp                                                              |
| <b>contact rating of auxiliary contacts according to UL</b>                           | A600 / Q600                                                       |
| <b>Short-circuit protection</b>                                                       |                                                                   |
| <b>design of the fuse link</b>                                                        |                                                                   |
| • for short-circuit protection of the main circuit                                    |                                                                   |
| — with type of coordination 1 required                                                | gG: 35A (690V,100kA), aM: 20A (690V,100kA), BS88: 35A (415V,80kA) |

|                                                                   |                                                                                                                                      |
|-------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| — with type of assignment 2 required                              | gG: 20A (690V, 100kA), aM: 16A (690V, 100kA), BS88: 20A (415V, 80kA)                                                                 |
| • for short-circuit protection of the auxiliary switch required   | gG: 10 A (500 V, 1 kA)                                                                                                               |
| <b>Installation/ mounting/ dimensions</b>                         |                                                                                                                                      |
| <b>mounting position</b>                                          | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| <b>fastening method</b>                                           | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715                                                             |
| <b>height</b>                                                     | 58 mm                                                                                                                                |
| <b>width</b>                                                      | 45 mm                                                                                                                                |
| <b>depth</b>                                                      | 73 mm                                                                                                                                |
| <b>required spacing</b>                                           |                                                                                                                                      |
| • with side-by-side mounting                                      |                                                                                                                                      |
| — forwards                                                        | 10 mm                                                                                                                                |
| — upwards                                                         | 10 mm                                                                                                                                |
| — downwards                                                       | 10 mm                                                                                                                                |
| — at the side                                                     | 0 mm                                                                                                                                 |
| • for grounded parts                                              |                                                                                                                                      |
| — forwards                                                        | 10 mm                                                                                                                                |
| — upwards                                                         | 10 mm                                                                                                                                |
| — at the side                                                     | 6 mm                                                                                                                                 |
| — downwards                                                       | 10 mm                                                                                                                                |
| • for live parts                                                  |                                                                                                                                      |
| — forwards                                                        | 10 mm                                                                                                                                |
| — upwards                                                         | 10 mm                                                                                                                                |
| — downwards                                                       | 10 mm                                                                                                                                |
| — at the side                                                     | 6 mm                                                                                                                                 |
| <b>Connections/ Terminals</b>                                     |                                                                                                                                      |
| <b>type of electrical connection</b>                              |                                                                                                                                      |
| • for main current circuit                                        | screw-type terminals                                                                                                                 |
| • for auxiliary and control circuit                               | screw-type terminals                                                                                                                 |
| • at contactor for auxiliary contacts                             | Screw-type terminals                                                                                                                 |
| • of magnet coil                                                  | Screw-type terminals                                                                                                                 |
| <b>type of connectable conductor cross-sections</b>               |                                                                                                                                      |
| • for main contacts                                               |                                                                                                                                      |
| — solid                                                           | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²                                                                                |
| — solid or stranded                                               | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²                                                                                |
| — finely stranded with core end processing                        | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)                                                                                          |
| • for AWG cables for main contacts                                | 2x (20 ... 16), 2x (18 ... 14), 2x 12                                                                                                |
| <b>connectable conductor cross-section for main contacts</b>      |                                                                                                                                      |
| • solid                                                           | 0.5 ... 4 mm²                                                                                                                        |
| • stranded                                                        | 0.5 ... 4 mm²                                                                                                                        |
| • finely stranded with core end processing                        | 0.5 ... 2.5 mm²                                                                                                                      |
| <b>connectable conductor cross-section for auxiliary contacts</b> |                                                                                                                                      |
| • solid or stranded                                               | 0.5 ... 4 mm²                                                                                                                        |
| • finely stranded with core end processing                        | 0.5 ... 2.5 mm²                                                                                                                      |
| <b>type of connectable conductor cross-sections</b>               |                                                                                                                                      |
| • for auxiliary contacts                                          |                                                                                                                                      |
| — solid or stranded                                               | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²                                                                                |
| — finely stranded with core end processing                        | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)                                                                                          |
| • for AWG cables for auxiliary contacts                           | 2x (20 ... 16), 2x (18 ... 14), 2x 12                                                                                                |
| <b>AWG number as coded connectable conductor cross section</b>    |                                                                                                                                      |
| • for main contacts                                               | 20 ... 12                                                                                                                            |
| • for auxiliary contacts                                          | 20 ... 12                                                                                                                            |
| <b>Safety related data</b>                                        |                                                                                                                                      |
| <b>product function</b>                                           |                                                                                                                                      |
| • mirror contact according to IEC 60947-4-1                       | Yes; with 3RH29                                                                                                                      |
| • positively driven operation according to IEC 60947-5-1          | No                                                                                                                                   |
| • suitable for safety function                                    | Yes                                                                                                                                  |
| suitability for use safety-related switching OFF                  | Yes                                                                                                                                  |
| <b>service life maximum</b>                                       | 20 a                                                                                                                                 |
| <b>test wear-related service life necessary</b>                   | Yes                                                                                                                                  |

|                                                               |                                                  |
|---------------------------------------------------------------|--------------------------------------------------|
| proportion of dangerous failures                              |                                                  |
| • with low demand rate according to SN 31920                  | 40 %                                             |
| • with high demand rate according to SN 31920                 | 73 %                                             |
| B10 value with high demand rate according to SN 31920         | 1 000 000                                        |
| failure rate [FIT] with low demand rate according to SN 31920 | 100 FIT                                          |
| ISO 13849                                                     |                                                  |
| device type according to ISO 13849-1                          | 3                                                |
| overdimensioning according to ISO 13849-2 necessary           | Yes                                              |
| IEC 61508                                                     |                                                  |
| safety device type according to IEC 61508-2                   | Type A                                           |
| Electrical Safety                                             |                                                  |
| protection class IP on the front according to IEC 60529       | IP20                                             |
| touch protection on the front according to IEC 60529          | finger-safe, for vertical contact from the front |
| Approvals Certificates                                        |                                                  |
| General Product Approval                                      |                                                  |



[Confirmation](#)



[KC](#)

|                          |     |                   |                   |                   |
|--------------------------|-----|-------------------|-------------------|-------------------|
| General Product Approval | EMV | Functional Safety | Test Certificates | Marine / Shipping |
|--------------------------|-----|-------------------|-------------------|-------------------|



[Type Examination Certificate](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



|                   |       |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



[Miscellaneous](#)

|       |         |                 |             |
|-------|---------|-----------------|-------------|
| other | Railway | Dangerous goods | Environment |
|-------|---------|-----------------|-------------|

[Confirmation](#)

[Special Test Certificate](#)

[Transport Information](#)



[Environmental Confirmations](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2015-1FB41>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2015-1FB41>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1FB41>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2015-1FB41&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2015-1FB41&lang=en)


### Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1FB41/char>

### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2015-1FB41&objecttype=14&gridview=view1>





last modified:

