



power contactor, AC-3e/AC-3, 7 A, 3 kW / 400 V, 3-pole, 24 V DC, 0.7-1.25\* Us, with integrated suppressor diode, auxiliary contacts: 1 NO, spring-loaded terminal, size: S00, suitable for PLC outputs, not expandable with auxiliary switch

|                                                                                                              |                            |
|--------------------------------------------------------------------------------------------------------------|----------------------------|
| product brand name                                                                                           | SIRIUS                     |
| product designation                                                                                          | Coupling contactor         |
| product type designation                                                                                     | 3RT2                       |
| <b>General technical data</b>                                                                                |                            |
| size of contactor                                                                                            | S00                        |
| product extension                                                                                            |                            |
| • function module for communication                                                                          | No                         |
| • auxiliary switch                                                                                           | No                         |
| power loss [W] for rated value of the current                                                                |                            |
| • at AC in hot operating state                                                                               | 0.6 W                      |
| • at AC in hot operating state per pole                                                                      | 0.2 W                      |
| • without load current share typical                                                                         | 2.8 W                      |
| type of calculation of power loss depending on pole                                                          | quadratic                  |
| insulation voltage                                                                                           |                            |
| • of main circuit with degree of pollution 3 rated value                                                     | 690 V                      |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 690 V                      |
| surge voltage resistance                                                                                     |                            |
| • of main circuit rated value                                                                                | 6 kV                       |
| • of auxiliary circuit rated value                                                                           | 6 kV                       |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V                      |
| shock resistance at rectangular impulse                                                                      |                            |
| • at DC                                                                                                      | 6,7g / 5 ms, 4,2g / 10 ms  |
| shock resistance with sine pulse                                                                             |                            |
| • at DC                                                                                                      | 10,5g / 5 ms, 6,6g / 10 ms |
| mechanical service life (operating cycles)                                                                   |                            |
| • of contactor typical                                                                                       | 30 000 000                 |
| reference code according to IEC 81346-2                                                                      | Q                          |
| Substance Prohibitance (Date)                                                                                |                            |
| SVHC substance name                                                                                          | Lead - 7439-92-1           |
| Weight                                                                                                       | 0.315 kg                   |
| <b>Ambient conditions</b>                                                                                    |                            |
| installation altitude at height above sea level maximum                                                      | 2 000 m                    |
| ambient temperature                                                                                          |                            |
| • during operation                                                                                           | -25 ... +60 °C             |
| • during storage                                                                                             | -55 ... +80 °C             |
| relative humidity minimum                                                                                    | 10 %                       |
| relative humidity at 55 °C according to IEC 60068-2-30 maximum                                               | 95 %                       |
| <b>Environmental footprint</b>                                                                               |                            |
| Environmental Product Declaration (EPD)                                                                      | Yes                        |

|                                                                        |                     |
|------------------------------------------------------------------------|---------------------|
| Global Warming Potential [CO2 eq] total                                | 153 kg              |
| Global Warming Potential [CO2 eq] during manufacturing                 | 1.42 kg             |
| Global Warming Potential [CO2 eq] during operation                     | 152 kg              |
| Global Warming Potential [CO2 eq] after end of life                    | -0.305 kg           |
| <b>Main circuit</b>                                                    |                     |
| <b>number of poles for main current circuit</b>                        | 3                   |
| <b>number of NO contacts for main contacts</b>                         | 3                   |
| <b>operating voltage</b>                                               |                     |
| • at AC-3 rated value maximum                                          | 690 V               |
| • at AC-3e rated value maximum                                         | 690 V               |
| <b>operational current</b>                                             |                     |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 18 A                |
| • at AC-1                                                              |                     |
| — up to 690 V at ambient temperature 40 °C rated value                 | 18 A                |
| — up to 690 V at ambient temperature 60 °C rated value                 | 16 A                |
| • at AC-3                                                              |                     |
| — at 400 V rated value                                                 | 7 A                 |
| — at 500 V rated value                                                 | 6 A                 |
| — at 690 V rated value                                                 | 4.9 A               |
| • at AC-3e                                                             |                     |
| — at 400 V rated value                                                 | 7 A                 |
| — at 500 V rated value                                                 | 6 A                 |
| — at 690 V rated value                                                 | 4.9 A               |
| • at AC-4 at 400 V rated value                                         | 6.5 A               |
| • at AC-5a up to 690 V rated value                                     | 15.8 A              |
| • at AC-5b up to 400 V rated value                                     | 5.8 A               |
| • at AC-6a                                                             |                     |
| — up to 230 V for current peak value n=20 rated value                  | 4 A                 |
| — up to 400 V for current peak value n=20 rated value                  | 4 A                 |
| — up to 500 V for current peak value n=20 rated value                  | 3.8 A               |
| — up to 690 V for current peak value n=20 rated value                  | 3.6 A               |
| • at AC-6a                                                             |                     |
| — up to 230 V for current peak value n=30 rated value                  | 2.7 A               |
| — up to 400 V for current peak value n=30 rated value                  | 2.7 A               |
| — up to 500 V for current peak value n=30 rated value                  | 2.5 A               |
| — up to 690 V for current peak value n=30 rated value                  | 2.4 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 2.5 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                     |
| • at 400 V rated value                                                 | 2.6 A               |
| • at 690 V rated value                                                 | 1.8 A               |
| <b>operational current</b>                                             |                     |
| • <b>at 1 current path at DC-1</b>                                     |                     |
| — at 24 V rated value                                                  | 15 A                |
| — at 60 V rated value                                                  | 15 A                |
| — at 110 V rated value                                                 | 1.5 A               |
| — at 220 V rated value                                                 | 0.6 A               |
| — at 440 V rated value                                                 | 0.42 A              |
| — at 600 V rated value                                                 | 0.42 A              |
| • <b>with 2 current paths in series at DC-1</b>                        |                     |
| — at 24 V rated value                                                  | 15 A                |
| — at 60 V rated value                                                  | 15 A                |
| — at 110 V rated value                                                 | 8.4 A               |
| — at 220 V rated value                                                 | 1.2 A               |
| — at 440 V rated value                                                 | 0.6 A               |
| — at 600 V rated value                                                 | 0.5 A               |
| • <b>with 3 current paths in series at DC-1</b>                        |                     |
| — at 24 V rated value                                                  | 15 A                |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 15 A<br>15 A<br>15 A<br>0.9 A<br>0.7 A                                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>● <b>at 1 current path at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> </ul> </li> <li>● <b>with 2 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> </ul> </li> <li>● <b>with 3 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul> | 15 A<br>0.35 A<br><br>15 A<br>3.5 A<br>0.25 A<br><br>15 A<br>15 A<br>15 A<br>1.2 A<br>0.14 A<br>0.14 A                                                                                                                                                                                                    |
| <b>operating power</b> <ul style="list-style-type: none"> <li>● at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>● at AC-3e <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                                                             | 1.5 kW<br>3 kW<br>3 kW<br>4 kW<br><br>1.5 kW<br>3 kW<br>3 kW<br>4 kW                                                                                                                                                                                                                                      |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>● at 400 V rated value</li> <li>● at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1.15 kW<br>1.15 kW                                                                                                                                                                                                                                                                                        |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=20 rated value</li> <li>● up to 400 V for current peak value n=20 rated value</li> <li>● up to 500 V for current peak value n=20 rated value</li> <li>● up to 690 V for current peak value n=20 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                          | 1.5 kVA<br>2.7 kVA<br>3.3 kVA<br>4.3 kVA                                                                                                                                                                                                                                                                  |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=30 rated value</li> <li>● up to 400 V for current peak value n=30 rated value</li> <li>● up to 500 V for current peak value n=30 rated value</li> <li>● up to 690 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                          | 1 kVA<br>1.8 kVA<br>2.2 kVA<br>2.9 kVA                                                                                                                                                                                                                                                                    |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>● limited to 1 s switching at zero current maximum</li> <li>● limited to 5 s switching at zero current maximum</li> <li>● limited to 10 s switching at zero current maximum</li> <li>● limited to 30 s switching at zero current maximum</li> <li>● limited to 60 s switching at zero current maximum</li> </ul>                                                                                                                                                                                                                                                                                        | 120 A; Use minimum cross-section acc. to AC-1 rated value<br>86 A; Use minimum cross-section acc. to AC-1 rated value<br>67 A; Use minimum cross-section acc. to AC-1 rated value<br>52 A; Use minimum cross-section acc. to AC-1 rated value<br>43 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>● at DC</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 10 000 1/h                                                                                                                                                                                                                                                                                                |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>● at AC-1 maximum</li> <li>● at AC-2 maximum</li> <li>● at AC-3 maximum</li> <li>● at AC-3e maximum</li> <li>● at AC-4 maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1 000 1/h<br>750 1/h<br>750 1/h<br>750 1/h<br>250 1/h                                                                                                                                                                                                                                                     |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                           |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | DC                                                                                                                                                                                                                                                                                                        |

|                                                                                       |                                                                      |
|---------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| <b>control supply voltage at DC rated value</b>                                       | 24 V                                                                 |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b> |                                                                      |
| • initial value                                                                       | 0.7                                                                  |
| • full-scale value                                                                    | 1.25                                                                 |
| <b>design of the surge suppressor</b>                                                 | suppressor diode                                                     |
| <b>closing power of magnet coil at DC</b>                                             | 2.8 W                                                                |
| <b>holding power of magnet coil at DC</b>                                             | 2.8 W                                                                |
| <b>closing delay</b>                                                                  |                                                                      |
| • at DC                                                                               | 25 ... 130 ms                                                        |
| <b>opening delay</b>                                                                  |                                                                      |
| • at DC                                                                               | 7 ... 20 ms                                                          |
| <b>arcing time</b>                                                                    | 10 ... 15 ms                                                         |
| <b>control version of the switch operating mechanism</b>                              | Standard A1 - A2                                                     |
| <b>Auxiliary circuit</b>                                                              |                                                                      |
| number of NO contacts for auxiliary contacts instantaneous contact                    | 1                                                                    |
| operational current at AC-12 maximum                                                  | 10 A                                                                 |
| <b>operational current at AC-15</b>                                                   |                                                                      |
| • at 230 V rated value                                                                | 10 A                                                                 |
| • at 400 V rated value                                                                | 3 A                                                                  |
| • at 500 V rated value                                                                | 2 A                                                                  |
| • at 690 V rated value                                                                | 1 A                                                                  |
| <b>operational current at DC-12</b>                                                   |                                                                      |
| • at 24 V rated value                                                                 | 10 A                                                                 |
| • at 48 V rated value                                                                 | 6 A                                                                  |
| • at 60 V rated value                                                                 | 6 A                                                                  |
| • at 110 V rated value                                                                | 3 A                                                                  |
| • at 125 V rated value                                                                | 2 A                                                                  |
| • at 220 V rated value                                                                | 1 A                                                                  |
| • at 600 V rated value                                                                | 0.15 A                                                               |
| <b>operational current at DC-13</b>                                                   |                                                                      |
| • at 24 V rated value                                                                 | 10 A                                                                 |
| • at 48 V rated value                                                                 | 2 A                                                                  |
| • at 60 V rated value                                                                 | 2 A                                                                  |
| • at 110 V rated value                                                                | 1 A                                                                  |
| • at 125 V rated value                                                                | 0.9 A                                                                |
| • at 220 V rated value                                                                | 0.3 A                                                                |
| • at 600 V rated value                                                                | 0.1 A                                                                |
| <b>contact reliability of auxiliary contacts</b>                                      | 1 faulty switching per 100 million (17 V, 1 mA)                      |
| <b>UL/CSA ratings</b>                                                                 |                                                                      |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                   |                                                                      |
| • at 480 V rated value                                                                | 4.8 A                                                                |
| • at 600 V rated value                                                                | 6.1 A                                                                |
| <b>yielded mechanical performance [hp]</b>                                            |                                                                      |
| • for single-phase AC motor                                                           |                                                                      |
| — at 110/120 V rated value                                                            | 0.25 hp                                                              |
| — at 230 V rated value                                                                | 0.75 hp                                                              |
| • for 3-phase AC motor                                                                |                                                                      |
| — at 200/208 V rated value                                                            | 1.5 hp                                                               |
| — at 220/230 V rated value                                                            | 2 hp                                                                 |
| — at 460/480 V rated value                                                            | 3 hp                                                                 |
| — at 575/600 V rated value                                                            | 5 hp                                                                 |
| <b>contact rating of auxiliary contacts according to UL</b>                           | A600 / Q600                                                          |
| <b>Short-circuit protection</b>                                                       |                                                                      |
| <b>design of the fuse link</b>                                                        |                                                                      |
| • for short-circuit protection of the main circuit                                    |                                                                      |
| — with type of coordination 1 required                                                | gG: 35A (690V, 100kA), aM: 20A (690V, 100kA), BS88: 35A (415V, 80kA) |
| — with type of assignment 2 required                                                  | gG: 20A (690V, 100kA), aM: 16A (690V, 100kA), BS88: 20A (415V, 80kA) |
| • for short-circuit protection of the auxiliary switch required                       | gG: 10 A (500 V, 1 kA)                                               |
| <b>Installation/ mounting/ dimensions</b>                                             |                                                                      |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715                                                             |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 70 mm                                                                                                                                |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 45 mm                                                                                                                                |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 73 mm                                                                                                                                |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 0 mm</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— at the side 6 mm</li> <li>— downwards 10 mm</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 6 mm</li> </ul> </li> </ul> |                                                                                                                                      |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                      |
| <b>type of electrical connection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                 | spring-loaded terminals<br>spring-loaded terminals<br>Spring-type terminals<br>Spring-type terminals                                 |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid 2x (0.5 ... 4 mm<sup>2</sup>)</li> <li>— solid or stranded 2x (0,5 ... 4 mm<sup>2</sup>)</li> <li>— finely stranded with core end processing 2x (0.5 ... 2.5 mm<sup>2</sup>)</li> <li>— finely stranded without core end processing 2x (0.5 ... 2.5 mm<sup>2</sup>)</li> </ul> </li> <li>• for AWG cables for main contacts 2x (20 ... 12)</li> </ul>                                                                                                                                    |                                                                                                                                      |
| <b>connectable conductor cross-section for main contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• solid 0.5 ... 4 mm<sup>2</sup></li> <li>• stranded 0.5 ... 4 mm<sup>2</sup></li> <li>• finely stranded with core end processing 0.5 ... 2.5 mm<sup>2</sup></li> <li>• finely stranded without core end processing 0.5 ... 2.5 mm<sup>2</sup></li> </ul>                                                                                                                                                                                                                                                                                                   |                                                                                                                                      |
| <b>connectable conductor cross-section for auxiliary contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• solid or stranded 0.5 ... 4 mm<sup>2</sup></li> <li>• finely stranded with core end processing 0.5 ... 2.5 mm<sup>2</sup></li> <li>• finely stranded without core end processing 0.5 ... 2.5 mm<sup>2</sup></li> </ul>                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                      |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded 2x (0,5 ... 4 mm<sup>2</sup>)</li> <li>— finely stranded with core end processing 2x (0.5 ... 2.5 mm<sup>2</sup>)</li> <li>— finely stranded without core end processing 2x (0.5 ... 2.5 mm<sup>2</sup>)</li> </ul> </li> <li>• for AWG cables for auxiliary contacts 2x (20 ... 12)</li> </ul>                                                                                                                                                                         |                                                                                                                                      |
| <b>AWG number as coded connectable conductor cross section</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• for main contacts 20 ... 12</li> <li>• for auxiliary contacts 20 ... 12</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                      |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                      |
| <b>product function</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                      |
| <ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> <li>• positively driven operation according to IEC 60947-5-1</li> <li>• suitable for safety function</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                            | No<br>No<br>Yes                                                                                                                      |
| suitability for use safety-related switching OFF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Yes                                                                                                                                  |
| <b>service life maximum</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 20 a                                                                                                                                 |

|                                                               |                                                  |
|---------------------------------------------------------------|--------------------------------------------------|
| test wear-related service life necessary                      | Yes                                              |
| proportion of dangerous failures                              |                                                  |
| • with low demand rate according to SN 31920                  | 40 %                                             |
| • with high demand rate according to SN 31920                 | 73 %                                             |
| B10 value with high demand rate according to SN 31920         | 1 000 000                                        |
| failure rate [FIT] with low demand rate according to SN 31920 | 100 FIT                                          |
| ISO 13849                                                     |                                                  |
| device type according to ISO 13849-1                          | 3                                                |
| overdimensioning according to ISO 13849-2 necessary           | Yes                                              |
| IEC 61508                                                     |                                                  |
| safety device type according to IEC 61508-2                   | Type A                                           |
| Electrical Safety                                             |                                                  |
| protection class IP on the front according to IEC 60529       | IP20                                             |
| touch protection on the front according to IEC 60529          | finger-safe, for vertical contact from the front |
| Approvals Certificates                                        |                                                  |
| General Product Approval                                      |                                                  |



[Confirmation](#)



[KC](#)

| General Product Approval | EMV | Functional Safety | Test Certificates |
|--------------------------|-----|-------------------|-------------------|
|--------------------------|-----|-------------------|-------------------|



[Type Examination Certificate](#)

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

[Miscellaneous](#)

| Marine / Shipping |
|-------------------|
|-------------------|



| other | Railway | Dangerous goods | Environment |
|-------|---------|-----------------|-------------|
|-------|---------|-----------------|-------------|

[Miscellaneous](#)

[Confirmation](#)

[Special Test Certificate](#)

[Transport Information](#)



[Environmental Confirmations](#)

| Further information |
|---------------------|
|---------------------|

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2015-2KB41>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2015-2KB41>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-2KB41>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2015-2KB41&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2015-2KB41&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-2KB41/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2015-2KB41&objecttype=14&gridview=view1>



