



power contactor, AC-3e/AC-3, 65 A, 30 kW / 400 V, 3-pole, 110 V AC, 50 Hz / 120 V, 60 Hz, with plugged-in varistor, auxiliary contacts: 2 NO + 2 NC, screw terminal, size: S2, captive auxiliary switch

|                                                                                                              |                             |
|--------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                           | SIRIUS                      |
| product designation                                                                                          | Power contactor             |
| product type designation                                                                                     | 3RT2                        |
| <b>General technical data</b>                                                                                |                             |
| size of contactor                                                                                            | S2                          |
| product extension                                                                                            |                             |
| • function module for communication                                                                          | No                          |
| • auxiliary switch                                                                                           | No                          |
| power loss [W] for rated value of the current                                                                |                             |
| • at AC in hot operating state                                                                               | 11.4 W                      |
| • at AC in hot operating state per pole                                                                      | 3.8 W                       |
| • without load current share typical                                                                         | 6.5 W                       |
| type of calculation of power loss depending on pole                                                          | quadratic                   |
| insulation voltage                                                                                           |                             |
| • of main circuit with degree of pollution 3 rated value                                                     | 690 V                       |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 690 V                       |
| surge voltage resistance                                                                                     |                             |
| • of main circuit rated value                                                                                | 6 kV                        |
| • of auxiliary circuit rated value                                                                           | 6 kV                        |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V                       |
| shock resistance at rectangular impulse                                                                      |                             |
| • at AC                                                                                                      | 9.8g / 5 ms, 6.5g / 10 ms   |
| shock resistance with sine pulse                                                                             |                             |
| • at AC                                                                                                      | 15.3g / 5 ms, 10.1g / 10 ms |
| mechanical service life (operating cycles)                                                                   |                             |
| • of contactor typical                                                                                       | 10 000 000                  |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000                   |
| • of the contactor with added auxiliary switch block typical                                                 | 10 000 000                  |
| reference code according to IEC 81346-2                                                                      | Q                           |
| Substance Prohibitance (Date)                                                                                |                             |
| SVHC substance name                                                                                          | Lead - 7439-92-1            |
| Weight                                                                                                       | 1.09 kg                     |
| <b>Ambient conditions</b>                                                                                    |                             |
| installation altitude at height above sea level maximum                                                      | 2 000 m                     |
| ambient temperature                                                                                          |                             |
| • during operation                                                                                           | -25 ... +60 °C              |
| • during storage                                                                                             | -55 ... +80 °C              |
| relative humidity minimum                                                                                    | 10 %                        |
| relative humidity at 55 °C according to IEC 60068-2-30                                                       | 95 %                        |

|                                                                   |                    |
|-------------------------------------------------------------------|--------------------|
| maximum                                                           |                    |
| <b>Main circuit</b>                                               |                    |
| number of poles for main current circuit                          | 3                  |
| number of NO contacts for main contacts                           | 3                  |
| operating voltage                                                 |                    |
| • at AC-3 rated value maximum                                     | 690 V              |
| • at AC-3e rated value maximum                                    | 690 V              |
| operational current                                               |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value       | 80 A               |
| • at AC-1                                                         |                    |
| — up to 690 V at ambient temperature 40 °C rated value            | 80 A               |
| — up to 690 V at ambient temperature 60 °C rated value            | 70 A               |
| • at AC-3                                                         |                    |
| — at 400 V rated value                                            | 65 A               |
| — at 500 V rated value                                            | 65 A               |
| — at 690 V rated value                                            | 47 A               |
| • at AC-3e                                                        |                    |
| — at 400 V rated value                                            | 65 A               |
| — at 500 V rated value                                            | 65 A               |
| — at 690 V rated value                                            | 47 A               |
| • at AC-4 at 400 V rated value                                    | 55 A               |
| • at AC-5a up to 690 V rated value                                | 70.4 A             |
| • at AC-5b up to 400 V rated value                                | 53.9 A             |
| • at AC-6a                                                        |                    |
| — up to 230 V for current peak value n=20 rated value             | 56.9 A             |
| — up to 400 V for current peak value n=20 rated value             | 56.9 A             |
| — up to 500 V for current peak value n=20 rated value             | 56.9 A             |
| — up to 690 V for current peak value n=20 rated value             | 47 A               |
| • at AC-6a                                                        |                    |
| — up to 230 V for current peak value n=30 rated value             | 38 A               |
| — up to 400 V for current peak value n=30 rated value             | 38 A               |
| — up to 500 V for current peak value n=30 rated value             | 38 A               |
| — up to 690 V for current peak value n=30 rated value             | 38 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value | 25 mm <sup>2</sup> |
| operational current for approx. 200000 operating cycles at AC-4   |                    |
| • at 400 V rated value                                            | 28 A               |
| • at 690 V rated value                                            | 22 A               |
| operational current                                               |                    |
| • at 1 current path at DC-1                                       |                    |
| — at 24 V rated value                                             | 55 A               |
| — at 60 V rated value                                             | 23 A               |
| — at 110 V rated value                                            | 4.5 A              |
| — at 220 V rated value                                            | 1 A                |
| — at 440 V rated value                                            | 0.4 A              |
| — at 600 V rated value                                            | 0.25 A             |
| • with 2 current paths in series at DC-1                          |                    |
| — at 24 V rated value                                             | 55 A               |
| — at 60 V rated value                                             | 45 A               |
| — at 110 V rated value                                            | 45 A               |
| — at 220 V rated value                                            | 5 A                |
| — at 440 V rated value                                            | 1 A                |
| — at 600 V rated value                                            | 0.8 A              |
| • with 3 current paths in series at DC-1                          |                    |
| — at 24 V rated value                                             | 55 A               |
| — at 60 V rated value                                             | 55 A               |
| — at 110 V rated value                                            | 55 A               |
| — at 220 V rated value                                            | 45 A               |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 2.9 A<br>1.4 A                                                                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>● <b>at 1 current path at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>● <b>with 2 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>● <b>with 3 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul> | 35 A<br>6 A<br>1 A<br>0.1 A<br>0.06 A<br><br>55 A<br>45 A<br>25 A<br>5 A<br>0.27 A<br>0.16 A<br><br>55 A<br>55 A<br>55 A<br>25 A<br>0.6 A<br>0.35 A                                                                                                                                                             |
| <b>operating power</b> <ul style="list-style-type: none"> <li>● at AC-2 at 400 V rated value</li> <li>● at AC-3               <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>● at AC-3e               <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                                                                         | 30 kW<br><br>18.5 kW<br>30 kW<br>37 kW<br>37 kW<br><br>18.5 kW<br>30 kW<br>37 kW<br>37 kW                                                                                                                                                                                                                       |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>● at 400 V rated value</li> <li>● at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 14.7 kW<br>20 kW                                                                                                                                                                                                                                                                                                |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=20 rated value</li> <li>● up to 400 V for current peak value n=20 rated value</li> <li>● up to 500 V for current peak value n=20 rated value</li> <li>● up to 690 V for current peak value n=20 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 22.6 kVA<br>39.4 kVA<br>49.2 kVA<br>56.1 kVA                                                                                                                                                                                                                                                                    |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=30 rated value</li> <li>● up to 400 V for current peak value n=30 rated value</li> <li>● up to 500 V for current peak value n=30 rated value</li> <li>● up to 690 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 15.1 kVA<br>26.2 kVA<br>32.8 kVA<br>45.3 kVA                                                                                                                                                                                                                                                                    |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>● limited to 1 s switching at zero current maximum</li> <li>● limited to 5 s switching at zero current maximum</li> <li>● limited to 10 s switching at zero current maximum</li> <li>● limited to 30 s switching at zero current maximum</li> <li>● limited to 60 s switching at zero current maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1 055 A; Use minimum cross-section acc. to AC-1 rated value<br>730 A; Use minimum cross-section acc. to AC-1 rated value<br>520 A; Use minimum cross-section acc. to AC-1 rated value<br>336 A; Use minimum cross-section acc. to AC-1 rated value<br>272 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>● at AC</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 5 000 1/h                                                                                                                                                                                                                                                                                                       |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>● at AC-1 maximum</li> <li>● at AC-2 maximum</li> <li>● at AC-3 maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 800 1/h<br>400 1/h<br>700 1/h                                                                                                                                                                                                                                                                                   |

|                                                                                       |                                                 |
|---------------------------------------------------------------------------------------|-------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at AC-3e maximum</li> </ul>                  | 700 1/h                                         |
| <ul style="list-style-type: none"> <li>• at AC-4 maximum</li> </ul>                   | 200 1/h                                         |
| <b>Control circuit/ Control</b>                                                       |                                                 |
| <b>type of voltage of the control supply voltage</b>                                  | AC                                              |
| <b>control supply voltage at AC</b>                                                   |                                                 |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> </ul>              | 230 V                                           |
| <ul style="list-style-type: none"> <li>• at 60 Hz rated value</li> </ul>              | 230 V                                           |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> |                                                 |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 0.8 ... 1.1                                     |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 0.8 ... 1.1                                     |
| <b>design of the surge suppressor</b>                                                 | with varistor                                   |
| <b>apparent pick-up power of magnet coil at AC</b>                                    |                                                 |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 212 VA                                          |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 188 VA                                          |
| <b>inductive power factor with closing power of the coil</b>                          |                                                 |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 0.69                                            |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 0.65                                            |
| <b>apparent holding power of magnet coil at AC</b>                                    |                                                 |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 18.5 VA                                         |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 16.5 VA                                         |
| <b>inductive power factor with the holding power of the coil</b>                      |                                                 |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 0.36                                            |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                          | 0.39                                            |
| <b>closing delay</b>                                                                  |                                                 |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                             | 10 ... 80 ms                                    |
| <b>opening delay</b>                                                                  |                                                 |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                             | 10 ... 18 ms                                    |
| <b>arcing time</b>                                                                    | 10 ... 20 ms                                    |
| <b>control version of the switch operating mechanism</b>                              | Standard A1 - A2                                |
| <b>Auxiliary circuit</b>                                                              |                                                 |
| <b>design of the auxiliary switch</b>                                                 | on the front, non-detachable                    |
| number of NC contacts for auxiliary contacts instantaneous contact                    | 2                                               |
| number of NO contacts for auxiliary contacts instantaneous contact                    | 2                                               |
| operational current at AC-12 maximum                                                  | 10 A                                            |
| <b>operational current at AC-15</b>                                                   |                                                 |
| <ul style="list-style-type: none"> <li>• at 230 V rated value</li> </ul>              | 6 A                                             |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> </ul>              | 3 A                                             |
| <ul style="list-style-type: none"> <li>• at 500 V rated value</li> </ul>              | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 690 V rated value</li> </ul>              | 1 A                                             |
| <b>operational current at DC-12</b>                                                   |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>               | 10 A                                            |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>               | 6 A                                             |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>               | 6 A                                             |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>              | 3 A                                             |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>              | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>              | 1 A                                             |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>              | 0.15 A                                          |
| <b>operational current at DC-13</b>                                                   |                                                 |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>               | 6 A                                             |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>               | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>               | 2 A                                             |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>              | 1 A                                             |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>              | 0.9 A                                           |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>              | 0.3 A                                           |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>              | 0.1 A                                           |
| <b>contact reliability of auxiliary contacts</b>                                      | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>                                                                 |                                                 |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                   |                                                 |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                              | 65 A<br>52 A                                                                                                                                                                      |
| <b>yielded mechanical performance [hp]</b> <ul style="list-style-type: none"> <li>• for single-phase AC motor <ul style="list-style-type: none"> <li>— at 110/120 V rated value</li> <li>— at 230 V rated value</li> </ul> </li> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 200/208 V rated value</li> <li>— at 220/230 V rated value</li> <li>— at 460/480 V rated value</li> <li>— at 575/600 V rated value</li> </ul> </li> </ul>                                                                                      | 5 hp<br>10 hp<br><br>20 hp<br>20 hp<br>50 hp<br>50 hp                                                                                                                             |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | A600 / Q600                                                                                                                                                                       |
| <b>Short-circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                   |
| <b>design of the fuse link</b> <ul style="list-style-type: none"> <li>• for short-circuit protection of the main circuit <ul style="list-style-type: none"> <li>— with type of coordination 1 required</li> <li>— with type of assignment 2 required</li> </ul> </li> <li>• for short-circuit protection of the auxiliary switch required</li> </ul>                                                                                                                                                                                                  | gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA)<br>gG: 125A (690V,100kA), aM: 63A (690V,100kA), BS88: 100A (415V,80kA)<br>gG: 10 A (500 V, 1 kA) |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                   |
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface                                              |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715                                                                                                          |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 114 mm                                                                                                                                                                            |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 55 mm                                                                                                                                                                             |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 174 mm                                                                                                                                                                            |
| <b>required spacing</b> <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                                                     |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                   |
| <b>type of electrical connection</b> <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>                                                                                                                                                                                                                                                                                                               | screw-type terminals<br>screw-type terminals<br>Screw-type terminals<br>Screw-type terminals                                                                                      |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for main contacts</li> </ul>                                                                                                                                                                                                                                                      | 2x (1 ... 35 mm²), 1x (1 ... 50 mm²)<br>2x (1 ... 25 mm²), 1x (1 ... 35 mm²)<br>2x (18 ... 2), 1x (18 ... 1)                                                                      |
| <b>connectable conductor cross-section for main contacts</b> <ul style="list-style-type: none"> <li>• finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                             | 1 ... 35 mm²                                                                                                                                                                      |
| <b>connectable conductor cross-section for auxiliary contacts</b> <ul style="list-style-type: none"> <li>• solid or stranded</li> <li>• finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                           | 0.5 ... 2.5 mm²<br>0.5 ... 2.5 mm²                                                                                                                                                |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                                 | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)                                                                                                                                       |

|                                                                |                                                                       |
|----------------------------------------------------------------|-----------------------------------------------------------------------|
| — finely stranded with core end processing                     | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| • for AWG cables for auxiliary contacts                        | 2x (20 ... 16), 2x (18 ... 14)                                        |
| <b>AWG number as coded connectable conductor cross section</b> |                                                                       |
| • for main contacts                                            | 18 ... 1                                                              |
| • for auxiliary contacts                                       | 20 ... 14                                                             |

| Safety related data                                                  |                                                  |
|----------------------------------------------------------------------|--------------------------------------------------|
| <b>product function</b>                                              |                                                  |
| • mirror contact according to IEC 60947-4-1                          | Yes                                              |
| • positively driven operation according to IEC 60947-5-1             | No                                               |
| • suitable for safety function                                       | Yes                                              |
| suitability for use safety-related switching OFF                     | Yes                                              |
| <b>service life maximum</b>                                          | 20 a                                             |
| <b>test wear-related service life necessary</b>                      | Yes                                              |
| <b>proportion of dangerous failures</b>                              |                                                  |
| • with low demand rate according to SN 31920                         | 40 %                                             |
| • with high demand rate according to SN 31920                        | 73 %                                             |
| <b>B10 value with high demand rate according to SN 31920</b>         | 1 000 000                                        |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b> | 100 FIT                                          |
| ISO 13849                                                            |                                                  |
| <b>device type according to ISO 13849-1</b>                          | 3                                                |
| <b>overdimensioning according to ISO 13849-2 necessary</b>           | Yes                                              |
| IEC 61508                                                            |                                                  |
| <b>safety device type according to IEC 61508-2</b>                   | Type A                                           |
| Electrical Safety                                                    |                                                  |
| <b>protection class IP on the front according to IEC 60529</b>       | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>          | finger-safe, for vertical contact from the front |

| Approvals Certificates   |
|--------------------------|
| General Product Approval |



[Confirmation](#)



[KC](#)

| General Product Approval | EMV | Functional Safety                            | Test Certificates                                  | Marine / Shipping                        |
|--------------------------|-----|----------------------------------------------|----------------------------------------------------|------------------------------------------|
|                          |     | <a href="#">Type Examination Certificate</a> | <a href="#">Type Test Certificates/Test Report</a> | <a href="#">Special Test Certificate</a> |
|                          |     |                                              |                                                    |                                          |

| Marine / Shipping | other                        |
|-------------------|------------------------------|
|                   | <a href="#">Confirmation</a> |
|                   |                              |
|                   |                              |
|                   |                              |
|                   |                              |

| Railway                                  | Dangerous goods                       | Environment                                 |
|------------------------------------------|---------------------------------------|---------------------------------------------|
| <a href="#">Special Test Certificate</a> | <a href="#">Transport Information</a> | <a href="#">Environmental Conformations</a> |

| Further information                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Information on the packaging<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a> |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2037-1CK64-3MA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2037-1CK64-3MA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2037-1CK64-3MA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2037-1CK64-3MA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2037-1CK64-3MA0&lang=en)


Characteristic: Tripping characteristics,  $I^2t$ , Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2037-1CK64-3MA0/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2037-1CK64-3MA0&objecttype=14&gridview=view1>





last modified:

