



Figure similar

SIPLUS S7-300 SM 331 8AI 40-pole based on 6ES7331-7NF10-0AB0 with conformal coating, -25...+60 °C, analog input isolated, 8 AI; +/-5/10V, 1-5 V, +/-20 mA, 0/4 to 20 mA, 16-bit, single rooting (60 V COM.), 4-channel operation: 10 ms, 8-channel operation: 23-95 ms, 1x 40-pole

General information	
based on	6ES7331-7NF10-0AB0
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	200 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	3 W
Analog inputs	
Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	75 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
<ul style="list-style-type: none"> Voltage 	Yes
<ul style="list-style-type: none"> Current 	Yes
<ul style="list-style-type: none"> Thermocouple 	No
<ul style="list-style-type: none"> Resistance thermometer 	No
<ul style="list-style-type: none"> Resistance 	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 0 to +10 V 	No
<ul style="list-style-type: none"> 1 V to 5 V <ul style="list-style-type: none"> Input resistance (1 V to 5 V) 	Yes 10 MΩ
<ul style="list-style-type: none"> 1 V to 10 V 	No
<ul style="list-style-type: none"> -1 V to +1 V 	No
<ul style="list-style-type: none"> -10 V to +10 V <ul style="list-style-type: none"> Input resistance (-10 V to +10 V) 	Yes 10 MΩ
<ul style="list-style-type: none"> -2.5 V to +2.5 V 	No
<ul style="list-style-type: none"> -250 mV to +250 mV 	No
<ul style="list-style-type: none"> -5 V to +5 V <ul style="list-style-type: none"> Input resistance (-5 V to +5 V) 	Yes 10 MΩ
<ul style="list-style-type: none"> -50 mV to +50 mV 	No
<ul style="list-style-type: none"> -500 mV to +500 mV 	No
<ul style="list-style-type: none"> -80 mV to +80 mV 	No
Input ranges (rated values), currents	
<ul style="list-style-type: none"> 0 to 20 mA 	Yes

— Input resistance (0 to 20 mA)	250 Ω
• -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	250 Ω
• -3.2 mA to +3.2 mA	No
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	250 Ω
Input ranges (rated values), thermocouples	
• Type B	No
• Type C	No
• Type E	No
• Type J	No
• Type K	No
• Type L	No
• Type N	No
• Type R	No
• Type S	No
• Type T	No
• Type U	No
• Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
• Cu 10	No
• Ni 100	No
• Ni 1000	No
• LG-Ni 1000	No
• Ni 120	No
• Ni 200	No
• Ni 500	No
• Pt 100	No
• Pt 1000	No
• Pt 200	No
• Pt 500	No
Input ranges (rated values), resistors	
• 0 to 150 ohms	No
• 0 to 300 ohms	No
• 0 to 600 ohms	No
• 0 to 6000 ohms	No
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; Unipolar: 15/15/15/15 bit; bipolar: 15 bit + sign/15 bit + sign/15 bit + sign/15 bit + sign
• Integration time, parameterizable	Yes; 23 / 72 / 83 / 95 ms
• Basic conversion time (ms)	10 ms (4-channel mode); 95/83/72/23 ms (8-channel mode)
• Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 Hz, combinations of 400, 60, 50 Hz
Encoder	
Connection of signal encoders	
• for voltage measurement	Yes
• for current measurement as 2-wire transducer	Yes; with external transmitter, current supply; possible with separate supply for transmitter
• for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.1 %; @ 0 ... +60 °C; ±0.2% @ -25 ... +60 °C
• Current, relative to input range, (+/-)	0.1 %; @ 0 ... +60 °C; ±0.2% @ -25 ... +60 °C
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.05 %
• Current, relative to input range, (+/-)	0.05 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable

Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm • Limit value alarm • Hardware interrupt 	<p>Yes; Parameterizable</p> <p>Yes; Parameterizable all channels (end of cycle interrupt is also supported across modules)</p> <p>Yes; Parameterizable, channels 0 to 7 (on exceeding limit value), at end of cycle</p>
Diagnoses	
<ul style="list-style-type: none"> • Diagnostic information readable 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) 	Yes
Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> • between the channels • between the channels, in groups of • between the channels and backplane bus • between the channels and the power supply of the electronics 	<p>No</p> <p>2</p> <p>Yes</p> <p>Yes</p>
Isolation	
Isolation tested with	500 V AC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
<ul style="list-style-type: none"> • EN 50121-4 • EN 50155 	<p>No</p> <p>No</p>
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. • max. 	<p>-25 °C; = Tmin</p> <p>60 °C; = Tmax</p>
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. • max. 	<p>-40 °C</p> <p>70 °C</p>
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. • Ambient air temperature-barometric pressure-altitude 	<p>5 000 m</p> <p>Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)</p>
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
<ul style="list-style-type: none"> — to biologically active substances according to EN 60721-3-3 — to chemically active substances according to EN 60721-3-3 — to mechanically active substances according to EN 60721-3-3 	<p>Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request</p> <p>Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 3S4 incl. sand, dust, *</p>
Use on ships/at sea	
<ul style="list-style-type: none"> — to biologically active substances according to EN 60721-3-6 — to chemically active substances according to EN 60721-3-6 — to mechanically active substances according to EN 60721-3-6 	<p>Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request</p> <p>Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 6S3 incl. sand, dust; *</p>
Usage in industrial process technology	
<ul style="list-style-type: none"> — Against chemically active substances acc. to EN 60654-4 — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 	<p>Yes; Class 3 (excluding trichlorethylene)</p> <p>Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)</p>
Remark	

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

* The supplied plug covers must remain in place over the unused interfaces during operation!

connection method

required front connector	40-pin
--------------------------	--------

Dimensions

Width	40 mm
Height	125 mm
Depth	120 mm

Weights

Weight, approx.	272 g
-----------------	-------

last modified:

