



SIMATIC S7-300, Analog module SM 334, Non-isolated 4 AI/2 AO, 1x 20-pole, Removing and inserting possible with active backplane bus

Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
Input current	
from supply and load voltage L+ (without load), max.	110 mA
from backplane bus 5 V DC, max.	55 mA
Power loss	
Power loss, typ.	3 W
Analog inputs	
Number of analog inputs	4
• For voltage measurement	4
permissible input voltage for voltage input (destruction limit), max.	20 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	5 ms
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
— Input resistance (0 to 10 V)	100 kΩ
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 Ω
Cable length	
• shielded, max.	200 m
Analog outputs	
Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	11 mA
Current output, no-load voltage, max.	15 V
Output ranges, voltage	
• 0 to 10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
Load impedance (in rated range of output)	

<ul style="list-style-type: none"> • with voltage outputs, min. 	5 kΩ
<ul style="list-style-type: none"> • with voltage outputs, capacitive load, max. 	1 μF
<ul style="list-style-type: none"> • with current outputs, max. 	300 Ω
<ul style="list-style-type: none"> • with current outputs, inductive load, max. 	1 mH
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	8 bit
<ul style="list-style-type: none"> • Integration time, parameterizable 	No
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	8 bit
<ul style="list-style-type: none"> • Conversion time (per channel) 	500 μs
Settling time	
<ul style="list-style-type: none"> • for resistive load 	0.3 ms
<ul style="list-style-type: none"> • for capacitive load 	3 ms
<ul style="list-style-type: none"> • for inductive load 	0.3 ms
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> • for voltage measurement 	Yes
<ul style="list-style-type: none"> • for current measurement as 2-wire transducer 	No
<ul style="list-style-type: none"> • for current measurement as 4-wire transducer 	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	0.9 %
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.8 %
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) 	0.6 %
<ul style="list-style-type: none"> • Current, relative to output range, (+/-) 	1 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	0.7 %
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.6 %
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) 	0.5 %
<ul style="list-style-type: none"> • Current, relative to output range, (+/-) 	0.5 %
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	No
Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> • between the channels and backplane bus 	No
Potential separation analog outputs	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	No
<ul style="list-style-type: none"> • between the channels and the power supply of the electronics 	Yes
Isolation	
Isolation tested with	500 V DC
connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	285 g

last modified:

