

product type designation



RF120C communication module

RFID communication module RF120C for SIMATIC S7-1200; 1 reader connectable; RS-422 or RS232.

suitability for operation

SIMATIC S7-1200 together with RF200/300/1000, MV300/400/500, MOBY D/U

transfer rate

| | |
|---|--------------|
| transfer rate / at the point-to-point connection / serial / maximum | 115.2 kbit/s |
|---|--------------|

interfaces

| | |
|---|-----------------------|
| design of the interface / for point-to-point connection | RS422/RS232 |
| number of readers / connectable | 1 |
| type of electrical connection | |
| • of the backplane bus | S7-1200 backplane bus |
| • for supply voltage | Screw terminals |
| design of the interface / to the reader / for communication | sub-D, 9-pin, female |

mechanical data

| | |
|---|----------------|
| material | Xantar MX 1094 |
| color | Ti-grey 24L01 |
| tightening torque / of the screw for securing the equipment / maximum | 0.45 N·m |

supply voltage, current consumption, power loss

| | |
|---|-------------|
| supply voltage / at DC | |
| • rated value | 24 V |
| • | 20 ... 30 V |
| consumed current | |
| • at DC / at 24 V / without connected devices / typical | 0.03 A |
| • from supply voltage 1L+ / maximum | 1 A |


ambient conditions

| | |
|--------------------------|--------------------------|
| ambient temperature | |
| • during operation | 0 ... 55 °C |
| • during storage | -40 ... +70 °C |
| • during transport | -40 ... +70 °C |
| protection class IP | IP20 |
| shock resistance | According to IEC 61131-2 |
| shock acceleration | 300 m/s² |
| vibrational acceleration | 100 m/s² |

design, dimensions and weights

| | |
|--|--------------|
| width | 30 mm |
| height | 100 mm |
| depth | 75 mm |
| net weight | 0.15 kg |
| fastening method | S7-1200 rack |
| wire length / for RS 422 interface / maximum | 1000 m |

product features, product functions, product components / general

| | | |
|---|---|--------------------------------|
| display version | 4 LEDs for reader connection, 1 LED for device status | |
| product function / addressable transponder file handler | No | |
| protocol / is supported | | |
| <ul style="list-style-type: none">• S7 communication | Yes | |
| product functions / management, configuration, engineering | | |
| type of parameterization | HSP, TO | |
| type of programming | ID profile, library with functions | |
| type of computer-switched communication | acyclic communication | |
| standards, specifications, approvals | | |
| certificate of suitability | CE, FCC, cULus, KCC, C-Tick, FM | |
| certificate of suitability | | |
| <ul style="list-style-type: none">• IECEx• for IECEx / as marking | Yes Ex: II 3G Ex nAA IIC T4 Gc | |
| MTBF | 196 a | |
| reference code | | |
| <ul style="list-style-type: none">• according to IEC 81346-2:2019 | KEC | |
| standards, specifications, approvals / Environmental Product Declaration | | |
| Environmental Product Declaration | Yes | |
| Global Warming Potential [CO2 eq] | | |
| <ul style="list-style-type: none">• total• during manufacturing• during operation• after end of life | 112.73 kg 15.07 kg 97.62 kg 0.042 kg | |
| further information / internet links | | |
| internet link | | |
| <ul style="list-style-type: none">• to website: Selection guide for cables and connectors• to web page: selection aid TIA Selection Tool• to web page: identification and localization systems• to web page: SiePortal• to website: Image database• to website: CAX-Download-Manager• to website: Industry Online Support | https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/ident https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com | |
| security information | | |
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7) | |
| Approvals / Certificates | | |
| General Product Approval | | |
| Declaration of Conformity | | |
| <div><div> EG-Konf.</div><div> CCC</div><div> UL</div><div> RCM</div><div></div></div> | | |
| General Product Approval | EMV | For use in hazardous locations |



[KC](#)



[FM](#)

[CCC-Ex](#)

Environment

[Confirmation](#)



last modified:

