## SM380A22810FP

# Hyde Park, Ultrasonic sensor, discrete, miniature flat profile, 12 24 V DC



### Main

Range of product	Hyde Park
Sensor type	Ultrasonic sensor
Series name	Superprox 300
Device short name	SM380
Sensor design	Flat form miniature
Type of sensing window	Fixed
Material	Plastic
Enclosure material	ULTEM
Front material	Glass epoxy
Type of output signal	Discrete
Discrete output function	1 NC
Wiring technique	4-wire
[Us] rated supply voltage	1224 V DC with overload and short-circuit protection
Supply voltage limits	1028 V DC
Discrete output type	PNP/NPN
Electrical connection	Remote male connector M12 4 pins, 152 mm cable length
Product specific application	Discrete proximity

#### Complementary

Complementary		
[Sn] nominal sensing distance	50.8 mm	
[Sd] sensing range	6.350.8 mm	
Maximum differential travel	0.7 mm	
Blind zone	6.4 mm	
Transmission frequency	500 kHz	
Repeat accuracy	0.7 %	
Beam angle	8 °	
Minimum size of detected object	Cylinder diameter 2.5 mm - up to 1 mm sensing distance	
Current consumption	25 mA	
Maximum switching current	100 mA with reverse polarity protection	
Height	7.62 mm	
Width	19.05 mm	
Depth	7.62 mm	
Length	33.02 mm	
Net weight	0.04 kg	

#### **Environment**

Product certifications	UL
Marking	CE
NEMA degree of protection	NEMA 4X (indoor use only)
IP degree of protection	IP67
Ambient air temperature for operation	-3070 °C
Ambient air temperature for storage	-40100 °C
Relative humidity	100 % without condensation
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz)
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27

Resistance to electromagnetic fields	10 V/m level 3 conforming to IEC 61000-4-3
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.415 cm
Package 1 Width	3.81 cm
Package 1 Length	8.415 cm
Package 1 Weight	117.934 g
Offer Sustainability California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defectator or other reproductive harm. For more information go to
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com
·	and Di-isodecyl phthalate (DIDP), which to cause birth defects or other reproduct www.P65Warnings.ca.gov
varranty	
Warranty	18 months