VM18VA2000Q

Hyde Park, Ultrasonic sensor, analog, voltage (V), 18 mm barrel, 15 24 V DC



Main

Range of product	Hyde Park
Sensor type	Ultrasonic sensor
Series name	Virtu VM18
Device short name	VM18
Sensor design	Cylindrical M18
Type of sensing window	Adjustable
Material	Plastic
Enclosure material	PBT
Front material	Glass epoxy
Type of output signal	Analog
ISO thread	M18 x 1
Wiring technique	4-wire
[Us] rated supply voltage	1524 V DC with overload and short-circuit protection
Supply voltage limits	1328 V DC
Analogue output range	010 V autoslope
Electrical connection	Male connector M12 4 pins

Complementary

508 mm
50.8508 mm
51 mm
300 kHz
1.27 %
5°
Cylinder diameter 2.5 mm - up to 200 mm sensing distance
40 mA
40 mA with reverse polarity protection
18 mm
18 mm
18 mm
77.62 mm
0.033 kg

Environment

UL	
CE	
NEMA 4X (indoor use only)	
IP67	
-3070 °C	
-4085 °C	
100 % without condensation	
+/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz)	
30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27	
10 V/m level 3 conforming to IEC 61000-4-3	
1 kV level 3 conforming to IEC 61000-4-4	
	CE NEMA 4X (indoor use only) IP67 -3070 °C -4085 °C 100 % without condensation +/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz) 30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27 10 V/m level 3 conforming to IEC 61000-4-3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.415 cm
Package 1 Width	1.27 cm
Package 1 Length	8.415 cm
Package 1 Weight	63.503 g
Package 1 Weight	63.503 g

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months