

EOS4 459 AH

Order Code: 1310552

Body Detection Safety Light Curtain with Automatic Restart, Extended Range



Safety level

Type 4 - PL e

Protected height (mm)

460

Resolution (mm)

90

Max. range (m)

20

Restart

Automatic

Functioning system

Emitter / Receiver

Technical Description

Compact Safety Light Curtain: Type 4, SIL 3, SILCL 3, PL e, Cat. 4

Cross Section: 28 x 30 mm

No blind area on one side

Hardware configuration: no programming necessary, easy to install and replace

Connection and configuration through M12 connectors

Unshielded cables up to 100 m can be used to connect the Safety Light Curtain

What's in the Box: Emitter, Receiver and Standard Fastening Brackets

Features

Safety level	Type 4 - PL e
Protected height (mm)	460
Resolution (mm)	90
Controlled height (mm)	450
Max. range (m)	20
Restart	Automatic
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
Operating temperature (°C)	- 20 ... 55
Response time (ms)	3
Number of beams	6
Max. length of the connection cables (m)	100
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and reverse polarity
Connections	M12 5-pole connectors
MTTFD (ISO13849) years	556,3
PFHD (IEC 61508)	1,08E-08
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
Safety functions	With external module
Detection	Body
Protective enclosures	None

EOS4 459 AH

Packaging dimensions HxLxW
(mm)

145 x 540 x 200

Product class

C

Custom tariff

85365019

Electrical data

Power supply (VDC)

24 ± 20%

Mechanical data

Overall height (mm)

536,5

Cross section dimensions (mm)

28 x 30

Degree of protection

IP65 - IP67


Fastening

Back slot with set of LE type brackets (included) or to the top
and lower end with swivel brackets SFB E (optional)

Gross weight (g)

1826,96

Technical drawings



Certificates

