

EOS4 902 AH

Order Code: **1310155**

Hand Detection Safety Light Curtain with Automatic Restart, Extended Range



Safety level

Type 4 - PL e

Protected height (mm)

910

Resolution (mm)

20

Max. range (m)

20

Restart

Automatic

Functioning system

Emitter / Receiver

Technical Description

Compact Safety Light Curtain: Type 4, SIL 3, SILCL 3, PL e, Cat. 4

Cross Section: 28 x 30 mm

No blind area on one side

Hardware configuration: no programming necessary, easy to install and replace

Connection and configuration through M12 connectors

Unshielded cables up to 100 m can be used to connect the Safety Light Curtain

What's in the Box: Emitter, Receiver and Standard Fastening Brackets

Features

Safety level	Type 4 - PL e
Protected height (mm)	910
Resolution (mm)	20
Controlled height (mm)	900
Max. range (m)	20
Restart	Automatic
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
Operating temperature (°C)	- 20 ... 55
Response time (ms)	13
Number of beams	90
Max. length of the connection cables (m)	100
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and reverse polarity
Connections	M12 5-pole connectors
MTTFD (ISO13849) years	338,5
PFHD (IEC 61508)	1,78E-08
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
Safety functions	With external module
Detection	Hand
Protective enclosures	None

EOS4 902 AH

Packaging dimensions HxLxW 145 x 1020 x 200

(mm)

Product class C

Custom tariff 85365019

Electrical data

Power supply (VDC) $24 \pm 20\%$

Mechanical data

Overall height (mm) 963

Cross section dimensions (mm) 28 x 30

Degree of protection IP65 - IP67

Fastening Back slot with set of LE type brackets (included) or to the top and lower end with swivel brackets SFB E (optional)

Gross weight (g) 3207,76

Technical drawings



Certificates

